

LBS-M Lithium Batteries Range

The LBS-M is the first of a new kind of battery range by Lithium Battery Solution. With emphasis on Lithium performances coupled with an innovative addition of a heating source, this product is the answer to your needs.

LBS-M modules are designed to be easily connected together to achieve greater specifications.



LITHIUM POWERED

Compared to conventional batteries, lithium-ion batteries recharge faster, are more durable as they last more than 20 years and are maintenance-free.



INNOVATIVE HEATING SOLUTION

This product is equipped with a heating film located under the batteries to allow charging at very low temperatures. The process of heating up the battery is automatically executed thanks to the connected charger and the monitoring system.



PERFORMANT BMS

The LBS-M is equipped with some of the most performant BMS in the industry. Coupled with its numerous internal sensors, the system provides real-time data and according adjustments without any user input. Many options are available.



FLEXIBLE & EVOLUTIVE SYSTEM










Designed to achieve any system size by connecting multiple LBS-M Modules to each other. Connections are made with soft connectors allowing safer use especially in vehicles.



COMPACT & LIGHTWEIGHT

The LBS-M packs a very high power density. At equal performances, our system is 4 to 5 times lighter than any of our competitor's lead-acid/AGM battery while being one of the most compact lithium solution in the industry.

THE IDEAL SOLUTION FOR :

-  Industrial
-  Commercial
-  Work trucks
-  Boats
-  Residential
-  RV
-  Van
-  Off-road
-  Solar

ELECTRICAL CHARACTERISTICS

Items	Unit	LBS-M 2X 12.8/25.6 400/200AH
Nominal voltage	[V]	12.8/25.6
Minimal operating voltage	[V]	11.2/22.4
Maximal operating voltage	[V]	14.4/28.8
Nominal capacity	[Ah]	200/400
Nominal energy	[kWh]	5.12
Group mode		2P4S
Number of cycles at 80% DOD		>3000
Volumetric energy density	[Wh/kg]	164
End of life residual capacity	[Ah]	160/320
Maximum continuous charge current	[A]	1C
Maximum continuous discharge current	[A]	1C
Maximum pulse discharge current (≤180s)	[A]	2C
Maximum Depth of Discharge	[%]	80
Insulation requirements	[MΩ]	≥20
Module heating method		Heating film controlled by BMS
Module cooling method		Natural cooling
Warranty		8 years*

MECHANICAL CHARACTERISTICS

Items	unit	LBS-M 2X 12.8/25.6 400/200AH
Length	[mm][in]	310.5/621 12.22/24.47
With	[mm][in]	204.5/ 409 8.05/ 16.1
Height	[mm][in]	185 7.28
Weight	[kg][lbs]	40 88.18
Volume	[dm^3]	7.18

CERTIFICATIONS



UN38.3

(may vary according to the model)

*5 years + 3 years prorated



Comes with an included battery management system of BMS-5BMS0

CONTACT US!

4490 Avenue des Industries

Laval, QC H7C 1A2 CANADA

Phone: (450) 973-4770

LITHIUM
BATTERY
SOLUTION CANADA

Designed in **Canada**