

Sterling-Power-USA

Waterproof Battery Chargers IP68

AQUANAUTIC Water proof range

8amp – 20amp PFC

WATERPROOF
and
SALTWATER
TESTED
IP68

- ✓ Lead acid sealed (AGM/Gel) battery selectable for max performance.
- ✓ Fully waterproof IP68, Ideal for boats exposed to splash or wash down.
- ✓ Both pos and neg. are fully isolated, enables 12V or 24V or 36v bank charging.
- ✓ Adaptive charging ensures max charge in the batteries.
- ✓ Extruded aluminum housing.
- ✓ Dynamic thermal output control.
- ✓ LED power and charge indicators.
- ✓ Built in protection distributed on demand.
- ✓ 4 stage charging curve, charge and condition batteries
- ✓ Pre wired waterproof loom for easy installation.
- ✓ Pre fused and gold plated terminals.
- ✓ Ignition protected, ideal for all boats.
- ✓ Available in up to 3 isolated output models
- ✓ Power Factor Corrected - 110-230 V A/C auto 40-70 Hz –
- ✓ 2 year warranty



Product	Battery Voltage	Input Voltage	Unit Size(LxWxH)	Weight	Part #
8 amp, 1 bank	12V	110v – 230v auto	6.8" x 7" x 2.5"	6.25 lbs.	PSP1281
8 amp, 2 bank	12V or 24V	110v – 230v auto	6.8" x 7" x 2.5"	6.25 lbs.	PSP1282
12 amp, 1 bank	12V	110v – 230v auto	7.5" x 7" x 2.5"	7.0 lbs.	PSP12121
12 amp, 2 bank	12V or 24V	110v – 230v auto	7.5" x 7" x 2.5"	7.0 lbs.	PSP12122
20 amp, 1 bank	12v	110v -230v auto	11.5" x 7" x 2.5"	8.5 lbs.	PSP12201
20 amp, 2 bank	12v or 24v	110v -230v auto	11.5" x 7" x 2.5"	8.5 lbs.	PSP12202
20 amp, 3 bank	12v or 24v or 36v	110v -230v auto	11.5" x 7" x 2.5"	8.5 lbs.	PSP12203