2. To make module LESS sensitive change the angle so that the arrow points more UP away from the ground.

angle so that the arrow points more DOWN towards the ground.

module is mounted 1. To make module MORE sensitive change the

style. To adjust sensitivity adjust the angle the

tested from large cruisers to sport bikes. Most sensitivity based on their bike and/or riding

an 'average' level based on a number of bikes customers find they want to adjust the

4. Adjusting Sensitivity When calibrated, the module sensitivity is set to

Turn bike power on. Press brake lever 5 times within first 10 seconds. Stay still. *Slow flashing: Module not level; remount. Fast flashing: Contact GearBrake support.




check brake light.

Solid = Success

Flash = Failure*



Mount module as level as possible. (+/- 20 deg)



Find mounting location away from heat and weather. Clean area.


Calibrate

Move bike to

level surface,


sit on it,

and stand it up.



Mount module flat or on edge with arrow





(input). 6.Connect Yellow wire on module to light side (output).

4. Cut brake power signal line. 5. Connect Blue wire on module to bike side

switched power.

3. Connect Red wire on module to +12V

2. Connect Green wire on module to Ground.


under the seat. Check your bike's wiring diagrams for correct wire colors.

Mounting. 1. Locate brake light wire harness. Typically

disconnect the bike's rear lighting connector, plug wire harness in between, and skip to

1. If you have a GearBrake wire harness simply







Questions? ICE TO YOUR BRAKE LIGHTS NI QQY

Call 502-771-0817 or email info@gearbrake.com

and play harness Visit www.gearbrake.com for information or to purchase a plug

the above limitations of exclusion may not apply to you. states do not allow the exclusion or limitation of incidental or consequential damages, so contingent, special or consequential damages arising from the use of our product. Some shall in no event be liable for death, injuries to persons or property, or for incidental, or accidents; repairs or alterations outside our facilities; or to lack of maintenance. We warranty does not apply to damage due directly or indirectly to misuse, abuse, negligence materials and workmanship for the period of its lifetime from the date of purchase. This Gearbrake warrants to the original purchaser that this product is free from defects in

from state to state. This warranty gives you specific legal rights and you may also have other rights which vary

PCT/US15/20844. duties, and risks associated therewith. Use only as intended. Patents Pending 14/659,627 τρε user shall assume all legal, personal injury risk, and liability and all other obligations, responsibility of the user to determine the suitability of the product for his or her use, and federal, state, and local laws before modifying your motorcycle. It is the sole and exclusive public highways, especially in states where highway safety laws may apply. Always check laws, rules and ordinances as well as other laws when used on motor vehicles operated on warranty. In addition, such installation and use may violate certain federal, state and local The installation of any attermarket part may void or otherwise adversely attect your factory

YOUR BRAKE LIGHTS

