

PRODUCT INFORMATION

- External j-box & spring mount clips for easy installation
- 3CCT version toggles between 3000k, 4000k & 5000k
- Compatible with most dimmers (e.g. Lutron / Leviton)
- Spring mount clips make installation easy
- Canless module does not require housing
- Made out of aluminium housing with PMMA lampshade
- 50 000 working hours
- Can decrease energy usage by 50%
- 25° degree adjustable



APPLICATION

- Offices • Hotels • Municipal • Hospitals & Clinics
- Commercial • Assisted Living • Retail • Facilities
- Schools & Universities





SPECIFICATION

ITEM No	Voltage (V)	Watt (W)	Lighting Color	CCT	Dimmable	Certificates	IP Range
LPG4RD9W3K-WH	120V	9W	Warm White	3000K	YES	ETL/ES	IP44
LPG4RD9W4K-WH			Natural White	4000K		ETL/ES	
LPG4RD9W5K-WH			Cool White	5000K		ETL/ES	
LPG4RD9W3CCT-WH			Changing colors	3CCT		ETL/ES	


PARAMETERS

Electrical Characteristics		Optical Characteristics	
Input Voltage	120V AC 50~60Hz	LED Type	SMD2835
Rated Power	9W	Brand of LED Chip	48pcs Taiwan Epistar
Replacement	9W=80W Halogen	Lumen	750lm
Installation of LED Driver	External	Life Span Based on 3hrs/day	45 years
Type of LED Driver	Constant current output	CRI	>80
Power Factor	0.95 ~0.98	Beam Angle	180 degree
Operating Temperature	-10°C-40°C	CCT	3CCT (3000k-4000k-5000k) & single CCT

INSTALLATION




DIMENSIONS




FEATURES



Angle ajustable 25°





Type	Value
Outer Diameter	5.55"/141mm
Cut Hole	4.25"/108mm
Height (Panel)	1.12"/28.5mm
Height (Junction Box)	1.35"/34.5mm
Length (Junction Box)	3.94"/100mm
Width (Junction Box)	2.75"/70mm
Adjustment Angle	25°