

TBX-440 TIG Brush Specifications



Model Designation	TIG Brush® TBX-440
Market Location	Australia and New Zealand
Feature	Details
Case Design	440 Series Injection Moulded IP65
Case Material	PC/ABS
Case Colour	Grey
Dimensions	245W x 190D x 370H
Weight (kg)	11kg
Mains Voltage	240VAC +5%/-10%, single phase
Input Current	Average of 2 amps
Operating Environment	-30 °C to +45 °C
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade, on any Grade and Power setting.
Application Selection	Rotary Switch
Applications	Sleep 0V Single Brush 11V PROPEL™ / Wide 14V
Mode Selection	Rotary Switch
Modes Available	Turbo Clean Polish / Etch Mark
Power Supply	Dynamic Power Transfer – 300VA
Maximum Operating Output Current	50 amps
Overload Control	Smart Circuit
Cables (2)	Red PVC insulated 4 metre with Handle Black PVC insulated 4 metre with Clamp
Brush Connection	Threaded M6
Maximum Brush size	Dual
Standards Compliance	CE, C-Tick N22274
<p><i>Note: Ensitech reserves the right to update product specifications at any time without notice.</i></p>	