


Gelcoat Premium Protection - Protection -

Product Description

Menzerna Gelcoat Premium Protection is a polymer sealant developed for the marine sector, especially for gelcoat surfaces. The latest technology enables long-lasting protection against environmental influences in combination with a simple application. In addition, it offers protection against adhesion and better sliding properties in water.

General Information: Category: Marine Product Group: Protection Storage: 5- 30°C, avoid frost and direct sun Colour: Blue Packaging 1L: 24015.261.080		Chemical Information: Density: e.g. 1,0 kg/l Viscosity: 4 – 10 Pa*s		
		Technical Information: Use together with: Wax Foam Pad, optional: microfiber cloth Orbital: Rotation speed recommendation: Lower speed range Pressure recommendation: Apply with low pressure		

Advantages

- Flawless surface for economical flow behavior
- Maintaining and increasing the value of the boat
- Effectively prevents adhesion even during long operating and holding times

Usage Recommendation

1. Before using it: clean the already shiny surface with the Control Cleaner to ensure that it is free of fat.
2. Shake the bottle and pour the product onto the polishing pad. Please note: the bigger the pad, the more Gelcoat Premium Protection you need.
3. Apply the long-lasting sealant together with the Wax Foam Pad.
4. To achieve a perfect result, we recommend using an orbital polishing machine and working in a cross-pattern. Apply light, steady pressure while applying the product and use the polishing machine at low machine speed.

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
 Industriestr. 25, D-76470 Ötigheim
 Tel.: +49-7222-9157-0
office@menzerna.com

5. After application: let the Gelcoat Premium Protection dry for at least 20 to 30 minutes. After drying remove residues with a premium microfiber cloth without applying pressure. Then let the sealant harden for at least 3 hours in a protected room.
6. Optional: For a longer sealing effect, it is possible after the product dried out, to apply several layers of the Menzerna Gelcoat Premium Protection.

Menzerna Marine System

	Surface Preparation	1. Heavy Cut	2. Medium Cut	3. Finish	4. Protection
Premium System	Liquid Sanding	Premium One Step Polish		Premium Gloss	Premium Protection
Polishing Tools	Lambswool Pads	Heavy Cut Foam Pad or Lambswool Pads		Soft Cut Foam Pad	Wax Foam Pad

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
 Industriestr. 25, D-76470 Ötigheim
 Tel.: +49-7222-9157-0
office@menzerna.com