



Issue date: 11/04/2021 Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: ROSE NOTE 1180509

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Aromatic Fragrances International, Inc

Company address: 85 Wansley Drive SE

Cartersville GA 30121 USA

Contact: Regulatory Affairs

E-Mail address: regulatory@afi-usa.com

Company phone: 770-334-3906

1.4 Emergency telephone number
Emergency phone: 770-334-3906

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of Flammable Liquid, Hazard Category 4

danger: Acute Toxicity - Oral Category 5

Skin Corrosion / Irritation Category 2 Eye Damage / Irritation Category 2 Sensitization - Skin Category 1

Hazardous to the Aquatic Environment - Acute Hazard Category 2
Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H227, Combustible liquid.

H303, May be harmful if swallowed.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H411, Toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning

Hazard statements: H227, Combustible liquid.

H303, May be harmful if swallowed.





Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H411, Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261, Avoid breathing vapour or dust.

P264, Wash hands and other contacted skin thoroughly after handling.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273. Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection.

P302/352, IF ON SKIN: Wash with plenty of soap and water.

P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P312, Call a POISON CENTRE or doctor/physician if you feel unwell.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P337/313, If eye irritation persists: Get medical advice/attention.

P362, Take off contaminated clothing and wash before reuse.

P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391, Collect spillage.

P403/235, Store in a well-ventilated place. Keep cool.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.



Pictograms:

2.3 Other hazards

Other hazards: None

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	%	GHS Classification
Phenethyl alcohol	60-12-8	711-5511%	Acute Tox. 4-Acute Tox. 5-Skin Irrit. 3-Eye Irrit. 2A; H302-H313-H316-H319
2-tert-Butylcyclohexyl acetate	88-41-5		Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 3-Aquatic Acute 2- Aquatic Chronic 2;H227-H303-H316-H411
Diethyl malonate	105-53-3	5-<10%	Flam. Liq. 4-Eye Irrit. 2A-Aquatic Acute 3;H227-H319- H402





Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

dl-Citronellol	106-22-9	5-<10%	Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H303-H313-H315-H317-H319-H401
d-Limonene	5989-27-5	5-<10%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1- Aquatic Acute 1-Aquatic Chronic 3;H226-H304-H315- H317-H400-H412
Isocyclocitral	1335-66-6	5-<10%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 3;H227-H303-H315-H317-H319-H401-H412
beta-lonone	14901-07-6	5-<10%	Skin Irrit. 3-Aquatic Acute 2-Aquatic Chronic 2;H316- H411
alpha,alpha-Dimethylphenethyl butyrate	10094-34-5	5-<10%	Aquatic Acute 2-Aquatic Chronic 2;H411
cis-3-Hexen-1-yl acetate	3681-71-8	1-<5%	Flam. Liq. 3-Skin Irrit. 3;H226-H316
Trichloromethyl phenyl carbinyl acetate	90-17-5	0.1-<1%	Skin Irrit. 2-Aquatic Acute 3-Aquatic Chronic 3;H315- H412
d,I-Isomenthone	491-07-6	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Skin Sens. 1B- Aquatic Acute 3;H227-H303-H315-H317-H402
Linalool	78-70-6	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402
3,7-Dimethyl-1-octanyl acetate	20780-49-8	0.1-<1%	Skin Irrit. 2-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H315-H317-H411

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May be harmful if swallowed.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.





Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high





Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Clear Colorless - 2 Very Pale Yellow free-flowing liquid without

sediment

Odour: Characteristic
Odour threshold: Not determined
pH: Not determined
Melting point / freezing point: Not determined
Initial boiling point / range: Not determined

Flash point: 69 °C

Evaporation rate: Not determined **Flammability (solid, gas):** Not determined

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Relative density: 0.9530 - 0.9630Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined **Viscosity:** Not determined **Explosive properties:** Not expected Oxidising properties: Not expected

9.2 Other information:

Refractive Index @ 20C: 1.4710 - 1.4810

Flash Point (Fahrenheit): 157 °F
Calculated VOC: 0.00
Color Range: 0-2

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.





Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity: Acute Toxicity - Oral Category 5

Acute Toxicity Oral 3862
Acute Toxicity Dermal >5000

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation:Skin Corrosion / Irritation Category 2Serious eye damage/irritation:Eye Damage / Irritation Category 2Respiratory or skin sensitisation:Sensitization - Skin Category 1

Germ cell mutagenicity:

Based on available data the classification criteria are not met.

Carcinogenicity:

Based on available data the classification criteria are not met.

Reproductive toxicity:

Based on available data the classification criteria are not met.

STOT-single exposure:

Based on available data the classification criteria are not met.

STOT-repeated exposure:

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available



Page 7 (9)

Issue date: 11/04/2021

Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class(es):	Sub Risk:	14.4. Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-tert- Butylcyclohexyl acetate, d-Limonene)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-tert- Butylcyclohexyl acetate, d-Limonene) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-tert- Butylcyclohexyl acetate, d-Limonene)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-tert-Butylcyclohexyl acetate, d-Limonene)	9	-	III

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

None additional

Section 16. Other information

Concentration % Limits: EH A2=22.92% EH A3=2.27% EH C2=67.97% EH C3=6.58% EH C4=51.

25% SCI 2=54.64% SCI 3=3.97% EDI 2A=20.96% SS 1=15.87%



AROMATIC FRAGRANCES

Issue date: 11/04/2021 Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

Total Fractional Values: EH A2=4.36 EH A3=43.97 EH C2=1.47 EH C3=15.19 EH C4=1.95 SCI

2=1.83 SCI 3=25.21 EDI 2A=4.77 SS 1=6.30

Key to revisions:

14.2. UN proper shipping name

Information about hazardous ingredients in the mixture

SECTION 3: Composition/information on ingredients

Key to abbreviations:

Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable liquid and vapour. H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 May be harmful in contact with skin. H316 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment.	Abbreviation	Meaning
Acute Tox. 5 Acute Toxicity - Oral Category 5 Aquatic Acute 1 Hazardous to the Aquatic Environment - Acute Hazard Category 1 Aquatic Acute 2 Hazardous to the Aquatic Environment - Acute Hazard Category 2 Aquatic Acute 3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 Aquatic Chronic 2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 Aquatic Chronic 3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2A Filam. Liq. 3 Filammable Liquid, Hazard Category 3 Filam. Liq. 4 Filammable Liquid, Hazard Category 4 H226 Filam. Liq. 4 Filammable Liquid, Hazard Category 4 H227 Combustible liquid H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes swin cause an allergic skin reaction. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H310 Harmful to aquatic life. H400 Harmful to aquatic life. H411 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H312 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment.	Acute Tox. 4	Acute Toxicity - Oral Category 4
Aquatic Acute 1 Hazardous to the Aquatic Environment - Acute Hazard Category 1 Aquatic Acute 2 Hazardous to the Aquatic Environment - Acute Hazard Category 2 Aquatic Chronic 2 Hazardous to the Aquatic Environment - Acute Hazard Category 3 Aquatic Chronic 2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 Aquatic Chronic 3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2A Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable Liquid, Hazard Category 4 H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed. H313 May be harmful in contact with skin. H316 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Acute Tox. 5	Acute Toxicity - Dermal Category 5
Aquatic Acute 2 Aquatic Acute 3 Aquatic Acute 3 Aquatic Chronic 2 Aquatic Chronic 2 Aquatic Chronic 3 Aparadous to the Aquatic Environment - Acute Hazard Category 3 Aquatic Chronic 3 Aparadous to the Aquatic Environment - Long-term Hazard Category 2 Aquatic Chronic 3 Aparadous to the Aquatic Environment - Long-term Hazard Category 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2A Flam. Liq. 3 Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H228 Flammable liquid and vapour. H227 Combustible liquid. H303 May be harmful if swallowed. H304 May be fatal if swallowed. H305 May be harmful in contact with skin. Causes skin irritation. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H401 Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. Flam Ago aver any form heat, sparks, open flames and hot surfaces No smoking. Flam Ago aver any from heat, sparks, open flames and hot surfaces No smoking. Flam Ago aver any from heat, sparks, open flames and hot surfaces No smoking. Flam Cause container tightly closed. Flam Cause and lighting equipment. Flam Cause container tightly closed. Flam Cause and lighting equipment. Flam Cause container and receiving equipment. Flam Cause container and receiving equipment. Flam Cause container and receiving equipment.	Acute Tox. 5	Acute Toxicity - Oral Category 5
Aquatic Acute 3 Hazardous to the Aquatic Environment - Acute Hazard Category 3 Aquatic Chronic 2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 Aquatic Chronic 3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2A Filam. Liq. 3 Filammable Liquid, Hazard Category 3 Filam. Liq. 4 Filammable Liquid, Hazard Category 4 H226 Filammable Liquid and vapour. Combustible liquid H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. F210 Keep away from heat, sparks, open flames and hot surfaces No smoking. F224 Use only non-sparking tools.	Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Chronic 2 Aquatic Chronic 3 Aquatic Chronic 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2 Flam. Liq. 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable Liquid, Hazard Category 4 H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and lighting equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Chronic 3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 Asp. Tox 1 Aspiration Hazard Category 1 Eye Irrit. 2A Eye Damage / Irritation Category 2A Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable liquid and vapour. H227 Combustible liquid. H300 Harmful if swallowed. H301 May be harmful if swallowed. H302 Harmful if swallowed and enters airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P230 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Asp. Tox 1	Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Eye Irrit. 2A Eye Damage / Irritation Category 2A Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable liquid and vapour. Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H313 May be harmful in contact with skin. Causes skin irritation. Causes mild skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Flam. Liq. 3 Flammable Liquid, Hazard Category 3 Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable liquid and vapour. H227 Combustible liquid. H300 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Asp. Tox 1	Aspiration Hazard Category 1
Flam. Liq. 4 Flammable Liquid, Hazard Category 4 H226 Flammable liquid and vapour. H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Eye Irrit. 2A	Eye Damage / Irritation Category 2A
H226 Flammable liquid and vapour. H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 May be harmful in contact with skin. H316 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	Flam. Liq. 3	Flammable Liquid, Hazard Category 3
H227 Combustible liquid. H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 May be harmful in contact with skin. H316 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H302 Harmful if swallowed. H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment.	H226	Flammable liquid and vapour.
H303 May be harmful if swallowed. H304 May be fatal if swallowed and enters airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. H223 Keep container tightly closed. H241 Use explosion-proof electrical, ventilating and lighting equipment. H242 Use enly non-sparking tools.	H227	Combustible liquid.
H304 May be fatal if swallowed and enters airways. H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H302	Harmful if swallowed.
H313 May be harmful in contact with skin. H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H303	May be harmful if swallowed.
H315 Causes skin irritation. H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H304	May be fatal if swallowed and enters airways.
H316 Causes mild skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H313	May be harmful in contact with skin.
H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H315	Causes skin irritation.
H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H316	Causes mild skin irritation.
H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H317	May cause an allergic skin reaction.
H401 Toxic to aquatic life. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H319	Causes serious eye irritation.
H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H400	Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H401	Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H402	Harmful to aquatic life.
P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H411	Toxic to aquatic life with long lasting effects.
P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	H412	Harmful to aquatic life with long lasting effects.
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.
P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools.	P233	Keep container tightly closed.
P242 Use only non-sparking tools.	P240	Ground/bond container and receiving equipment.
	P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243 Take precautionary measures against static discharge.	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.



Version: 2 (10/28/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: ROSE NOTE 1180509

Version: 2

P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.