The HMT V100T offers high performance, low maintenance industrial drilling with an all-day broaching capacity up to 4" diameter.

Its powerful forward /reverse, variable speed, geared Eibenstock motor will tap holes up to 1-1/4" and can be used with the VersaDrive® blind hole tapping system up to 1-1/4". The V100T is also fully rated for reaming and countersinking. Supplied with a coolant fed arbor.

7/16" - 4" TCT





- All-day broaching capability up to 4" diameter
- Forward and reverse
- Variable speed motor

CUTTER SIZE RANGE

WARRANTY

- Variable Torque control

TECHNICAL SPECIFICATIONS

MAX CUTTER CAPACITY 4" TCT DEPTH OF CUT 8" TWIST DRILL CAPACITY 1 1/4 COUNTERSINKING 2" REAMING 1 1/16 MAX TAP CAPACITY 1 1/4 LENGTH 13 1/2 WIDTH (Inc Handles) 9 1/2" HEIGHT (Min-Max) 17 1/2" - 29" STROKE 11" WEIGHT 54 lb 8 1/2" X 4 1/2" MAGNET (L X W) MAGNETIC ADHESION 4850 lb MOTOR POWER 1800W TOTAL POWER 1900W SPEED RPM (No Load) 60 - 140 / 200 - 470 SPINDLE MT3 ARBOR 34" Weldon COOLANT SYSTEM Gravity Oil Fed



2 Year (When registered)





Part No	Contents
850100-P-110US	V100T Magnetic Drill Kit - 110v





