

HMT V60T Pipe Magnet Drill

HOLEMAKER TECHNOLOGY
HMT

The V60T Pipe Magnet Drill offers all the advantages of the standard V60T with the added benefit of a pipe compatible magnetic base.

Two switched permanent magnets are secured to swivelling mounting points and can be positioned as needed, allowing use on tubes and piping with a minimum diameter of 3-5/32". This also allows use on many contoured surfaces and internal use on large pipes.

Magnets can also be positioned horizontally for use as a standard machine on flat surfaces.

FEATURES & BENEFITS

- Use on both contoured and flat surfaces
- Two switched permanent magnets with individual swivel action
- Use on pipe/tubing internally and externally as needed (min diameter 3-5/32")
- Supplied with coolant fed arbor

TECHNICAL SPECIFICATIONS

CUTTER SIZE RANGE	7/16" - 2-3/8" TCT
MAX CUTTER CAPACITY	2-3/8" TCT
DEPTH OF CUT	6"
TWIST DRILL CAPACITY	3/4"
COUNTERSINKING	1-1/2"
REAMING	3/4"
MAX TAP CAPACITY	3/4"
LENGTH	12-1/2"
WIDTH (Inc Handles)	8-1/2"
HEIGHT (Min-Max)	16-1/2" - 25"
STROKE	8-1/2"
WEIGHT	41.89 lb
MAGNET (L X W)	10-1/2" x 9-1/2" x 3-1/4"
MAGNETIC ADHESION	1896 lb
MOTOR POWER	1150w
TOTAL POWER	1270w
SPEED RPM (No Load)	100 - 250 / 180 - 450
SPINDLE	MT2
ARBOR	3/4" Weldon
COOLANT SYSTEM	Gravity Oil Fed
WARRANTY	2 Year (When registered)



Part No	Contents
850060-T-110US	V60T PIPE Twin Magnet Drill Kit 110v

Supplied with case, VersaDrive® Rapid-Lock adapter, Morse taper broaching arbor, handles, restraint strap, heavy duty metal guard & gravity fed coolant system.

