The HMT V6oT is designed to meet a need in the market for a high-performance, low-maintenance, industrial quality portable drilling unit.

The powerful forward/reverse, variable speed, Eibenstock motor will tap holes up to 3/4" diameter.

The V60T is also fully rated for reaming & countersinking. Advanced British electromagnets provide enhanced magnet hold for exceptional safety and stability. Supplied with a coolant fed arbor.



FEATURES & BENEFITS

- All-day broaching capability up to 2-3/8" diameter
- Forward and reverse
- Variable speed motor
- 8-1/2" Stroke

SPINDI F

ARBOR

TECHNICAL SPECIFICATIONS

CUTTER SIZE RANGE 7/16" - 2-3/8" TCT MAX CUTTER CAPACITY 2-3/8" TCT DEPTH OF CUT 6" TWIST DRILL CAPACITY 3/4 COUNTERSINKING 11/2 3/4" REAMING MAX TAP CAPACITY 3/4" STROKE 8-1/2 LENGTH 12-1/2 WIDTH (Inc Handles) 8-1/2" HEIGHT (Min-Max) 15 - 24 WFIGHT 39.5 lb MAGNET (L X W) 8" x 4" MAGNETIC ADHESION 3860 lb MOTOR POWER 1150W TOTAL POWER 1270W SPEED RPM (No Load) 100 - 250 / 180 - 450



MT₂

¾" Weldon



Part No	Contents
850060-P-110US	V60T Magnetic Drill Kit - 110v







