















CONTROLLERS - Selection Guide



COST EFFECTIVE FAMILIES (Temperature, PID PWM Output)

ADVANCED FEATURES FAMILIES (Universal Input, RS485 Modbus, Ramp & Soaks, PID Analog Output, 4-20 mA retransmission, Digital Input, Square Root)

	 N1030	 N1030T	 N1040	 N1040T	 N1020	 N480D	 N960	 N2020	 N120	 N3000	 N1200	 N1200-HC	 N2000	 N2000-S
Controller Type	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Process	Process	Process	Process	Process	Process
PID Output Control Mode	PWM	PWM	PWM	PWM	PWM	PWM & Analog (optional)	PWM & Analog (optional)	PWM & Analog (optional)	PWM	PWM & Analog (optional)	PWM & Analog	PWM & Analog	PWM & Analog	PWM & Analog
Auto Tune PID	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Self-Adaptive PID					✓				✓	✓	✓	✓	✓	✓
Control Loops	1	1	1	1	1	1	1	1	2	1	1	2	1	1
Control Action	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat & Cool with Overlap	Heat or Cool	Heat or Cool	Heat & Cool with Overlap	Heat or Cool	Servo
Relay Output	1	1	Up to 3	Up to 3	1	Up to 3	2	2	✓	Up to 4	Up to 3	Up to 3	Up to 4	Up to 4
Pulse Output	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Analog Output						Optional	✓	Optional		✓	✓	✓	✓	✓
Ramp to Soak Function					✓	✓	✓	✓		✓	✓	✓	✓	✓
Ramp & Soak Programs/ Segments						1/9	1/9	1/9	20/ 9	7/ 7	20/9	20/9	7/7	7/7
Soft-Start Function			✓	✓	✓			✓	✓	✓	✓	✓	✓	✓
Bumpless Function								✓	✓	✓	✓	✓	✓	✓
Manual Operation								✓	✓	✓	✓	✓	✓	✓
Display	Double	Double	Double	Double	Single	Double	Double	Double	Double	Double	Double	Double	Double	Double
Input Type	J, K, T, and Pt100				J, K, T, R, S, E, N, Pt100 and 0-50 mV	J, K, T, R, S, E, N and Pt100		J, K, T, and Pt100	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV, 0-5 V, 0-10 V	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV and 0-5 V	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV, 0-5 V and 0-10 V		J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV and 0-5 V	J, K, T, R, S, N, Pt100, 4-20 mA, 0-50m V and 0-5 V
Input Resolution Levels	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	20000
Input Sample Rate	5 sps	5 sps	55 sps	55 sps	55 sps	55 sps	55 sps	20 sps	55 sps	10 sps	55 sps	55 sps	10 sps	5 sps
Detection Sensor Break	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Detection PID Loop Break			✓	✓	✓			✓	✓			✓	✓	
Detection Heater Break									✓					
Alarm Number	1	1	2	2	2	2	2	2	2	4	Optional 4		4	2
Alarm Types	Low, High, Dif, DifLo, DifHi and InputErr				Low, High, Dif, DifLo, DifHi, Ton, TEnd and InputErr	Low, High, Dif, DifLo, DifHi, EndSoak, Event and InputErr		Low, High, Dif, DifLo, DifHi, Event and InputErr	Low, High, Dif, DifLo, DifHi, Event and InputErr		Low, High, Dif, DifLo, DifHi, ResistFail, Event and Input Error		Low, High, Dif, DifLo, DifHi, Event and InputErr	Low, High, Dif, DifLo, DifHi, ResistFail, Event and Input Error
Digital Input									✓	✓	✓	✓	✓	✓
Remote Setpoint Input									✓	✓	✓	✓	✓	✓
Setpoint Retransmission								✓		✓	✓	✓	✓	✓
Square Root										✓	✓	✓	✓	✓
Timer		✓		✓	✓									
Data Logger Function									Optional					
Password Protection	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓
Auxiliary 24V Power Supply									✓	✓	✓	✓	✓	✓
RS485 Modbus RTU			Optional		Optional				✓	Optional	Optional	Optional	Optional	Optional
USB			✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
CE Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
UL Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Frontal IP65	✓	✓	✓	✓	✓	✓	✓	✓	n/a	✓	✓	✓	✓	✓
Power Supply	100-240 Vac/dc or 12-24 Vdc (Optional)				100-240 Vac/dc	100-240 Vac/dc or 12-24 Vdc (Optional)		100-240 Vac/dc	100-240 Vac/dc or 12-24 Vdc (Optional)					
Panel Format	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 24 DIN 1/32	48 x 48 DIN 1/16	96 x 96 DIN 1/4	96 x 48 DIN 1/8	Board only Dual Display	96 x 96 DIN 1/4	48 x 48 DIN 1/16	48 x 48 DIN 1/16	96 x 48 DIN 1/8	96 x 48 DIN 1/8