



Xitrix GX3R-X670

The New King of Gaming PC

- AMD Ryzen™ 7000 Series Processor
- AMD X670 Chipset Motherboard
- Dual Channel DDR5 4*SMD DIMMs with AMD EXPO™ & Intel® XMP Memory Module Support
- Next Generation Storage : 1*PCIe 5.0 x4 and 3*PCIe 4.0 x4 M.2 Connectors
- Fast 2.5GbE LAN with Bandwidth Management; AMD Wi-Fi 6E RZ616



MODEL Xitrix® GXR-AMD Gaming PC

Supported Processors	AMD Ryzen™ 5 7600X (32MB Cache 4.7GHz Up to 5.3GHz 6 Cores 12Threads) Desktop Processors AMD Ryzen™ 7 7700X (32MB Cache 4.5GHz Up to 5.4GHz 8 Cores 16Threads) Desktop Processors AMD Ryzen™ 9 7900X (64MB Cache 4.7GHz Up to 5.6GHz 12 Cores 24Threads) Desktop Processors AMD Ryzen™ 9 7950X (64MB Cache 4.5GHz Up to 5.7GHz 16 Cores 32Threads) Desktop Processors
Core Chipset	AMD X670 Chipset
Operating System	64bit Microsoft® Windows® 11Home or Professional
System Memory	Support for DDR5 6600(OC)/6400(OC)/6200(OC)/6000(OC)/5600(OC)/5200/4800/4400 MHz memory modules 4 x DDR5 DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for AMD Extended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules
Supported Graphics	Support for Up to nVidia GeForce RTX-4090 Graphic Cards or NVIDIA RTX A4000 Support for AMD CrossFire™ and 2-Way AMD CrossFire™ technologies
Slots	1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16) 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4) 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x2 (PCIEX2)
Storage	1 x M.2 connector (Socket 3, M key, type 25110/2280 PCIe 5.0(Note) x4/x2 SSD support) (M2A_CPU) 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU) 2 x M.2 connectors (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2C_SB, M2D_SB) 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices and SATA storage devices
Audio	Realtek® High Definition 2/4/5.1/7.1-channel Audio; Support for S/PDIF Out
Peripheral Interfaces	Front Ports: 1 x USB 3.1 Gen 2Type-C, 2 x USB 3.0, HD Audio Rear Ports: 1 x Flash Plus button, 2 x SMA antenna connectors (2T2R), 1 x HDMI 2.0 port, 6 x USB 3.2 Gen 1 ports, 4 x USB 2.0/1.1 ports, 2 x USB 3.2 Gen 2 Type-A ports (red), 1 x USB Type-C® port, with USB 3.2 Gen 2x2 support, 1 x RJ-45 port, 3 x audio jacks
Networking Support	Built in 2.5 Gigabit LAN 10/100/1000/2500 Mb/s Built in AMD Wi-Fi 6E RZ616; Bluetooth 5.2 + High speed class II
Chassis Type Dimension Power Supply	Xitrix GX3 Elite EATX GamingChassis (side Tempered Glass); Product: 537 x 270 x 528 mm; Package: 590 x 550 x 240 mm 800 WATTS High Efficiency 80Plus Gold Power Supply Fully Modular; Up to 1300watts Power Supply
Thermal Solution Compatibility	Front: 3 x 120 mm RGB Cooling Fan Rear 1 x 120mm RGB Cooling Fan Top: 240MM Radiator for AIO Liquid Cooling System
RGB	RGB LED Header; Addressable RGB Lighting
Standard Warranty and Service Offerings	Service Offerings 3-Year Limited Parts Warranty & Technical Support Policy; 1-Year Next Business Day On-site Service Optional 3 Years Next Business Day on-site



XITRIX COMPUTER CORPORATION
23 Detroit St. Cubao, Quezon City
Tel: (632) 721 9999 Email: sales@xitrix.net
Fax: (632) 570 8034 Support@xitrix.net

