

## Xitrix GL2R Gaming PC

Maximum Performance – Minimal Footprint

- Support AMD Ryzen™ 5000 Series Desktop Processors
- Up to 64GB Memory; M.2 PCIe 4.0 SSD and 2.5" HDD
- Supports Up to GTX, RTX-30 and RTX40 Series Graphic Cards
- Gigabit LAN and 802.11ac WiFi Module
- 700watts or 1000 watts Power Supply



### MODEL Xitrix® GL2R AMD Gaming PC

<b>Supported Processors</b>	AMD Ryzen™ 5000 Series Desktop Processors
<b>Core Chipset</b>	AMD B550 Chipset
<b>Operating System</b>	Microsoft® Windows® 10 and Windows™ 11 64Bit (Home and Professional)
<b>System Memory</b>	Two DDR4 DIMM Slots; Dual Channel DDR4 Memory Technology Support for up to 64GB of system memory; 3600MHz Supports Extreme Memory Profile (XMP) memory modules
<b>Supported Graphics</b>	nVidia GeForce RTX4070Ti (12GB GDDR6X / 21 Gbps / 192-bit) nVidia GeForce RTX-3060 (12GB GDDR6 / 15 Gbps / 192-bit) nVidia GeForce RTX-3050 (8GB GDDR6 / 14 Gbps / 128-bit) nVidia GeForce GTX-1650 (4GB GDDR6 / 12 Gbps / 128-bit)
<b>Slots</b>	1 x PCI Express x16 Gen 4 Graphic Slot 1 x M.2 Socket, supports type 2280 SATA3 6.0 Gb/s PCIe Gen4x4 (64 Gb/s) modes 1 x Vertical M.2 Socket (Key E) with the bundled WiFi-802.11ac PCIe WiFi module (on the rear I/O)
<b>Hard Drive</b>	Up to 2 x 2.5inch SATA Solid State Drive or HDD Up to 1 x M.2 Socket SSD Solid State Drive
<b>Audio</b>	7.1 CH HD Audio (Realtek ALC887/897 Audio Codec); Supports Surge Protection
<b>Peripheral Interfaces</b>	Front / Top Ports: USB 3.2 Gen1 Type-A Ports ; USB Type C Port; 2x Audio Jack Rear Ports: - 2 x Antenna Ports; 1 x PS/2 Mouse/Keyboard Port - 1 x HDMI Port; 1 x DisplayPort 1.4 - 2 x USB 2.0 Ports (Supports ESD Protection) - 3 x USB 3.2 Gen1 Type-A Ports (Supports ESD Protection) - 1 x USB 3.2 Gen1 Type-C Port (Supports ESD Protection) - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jacks: Line in / Front Speaker / Microphone
<b>LAN Support</b>	Integrated 10/100/1000Gigabit LAN (Supports Wake-On-LAN , Lightning/ESD Protection, Energy Efficient Ethernet 802.3az) 802.11ac WiFi Module Dual-Band (2.4/5 GHz) ; Built in High speed class II Bluetooth
<b>Chassis Type Dimension Power Supply</b>	Mini ITX Chassis with Dual Side Panel Doors design (L)426*(W)170*(H)325mm Standard: 700 WATTS High Efficiency 80Plus Gold Power Supply Optional: 1000 WATTS High Efficiency 80Plus Gold Power Supply
<b>System Cooling</b>	2 x 120mm RGB Cooling Fan ( Front) 2 x 120mm RGB Cooling Fan ( Top) Supports 240mm AIO RGB Liquid Cooling System
<b>Standard Warranty and Service Offerings</b>	Service Offerings 3-Year Limited Parts Warranty & Technical Support Policy; 1-Year Next Business Day On-site Service Optional 3 Years Next Business Day on-site



**XITRIX COMPUTER CORPORATION**  
23 Detroit St. Cubao, Quezon City  
Tel: (632) 721 9999 Email: sales@xitrix.net  
Fax: (632) 570 8034 Support@xitrix.net

