



Xitrix GL2R D5 Gaming PC

Maximum Performance – Minimal Footprint

- Latest AMD Ryzen™ 7000 Series Desktop Processors
- Up to 96GB DDR5 Memory; PCIe 5.0 M.2 Next Gen Storage
- Supports Up to GTX, RTX-30 and RTX40 Series Graphic Cards
- Intel® 2.5GbE LAN & Wi-Fi 6E 802.11ax
- 700watts or 1000 watts Power Supply

AMD
RYZEN
7000 Series



MODEL Xitrix® GL2R D5 AMD Gaming PC

Supported Processors	AMD Ryzen™ 7000 Series Desktop Processors
Core Chipset	AMD B650 Chipset (B650I AORUS MINI ITX Gaming Motherboard)
Operating System	Microsoft® Windows® Windows™ 11 64Bit (Home and Professional)
System Memory	Support for DDR5 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s memory modules 2 x DDR5 DIMM sockets supporting up to 96 GB (48 GB single DIMM capacity) of system memory Dual channel memory architecture Support for AMD Extended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules
Supported Graphics	nVidia GeForce RTX-4060, 4060Ti and RTX4070Ti nVidia GeForce RTX-3050 (8GB GDDR6 / 14 Gbps / 128-bit) nVidia GeForce GTX-1650 (4GB GDDR6 / 12 Gbps / 128-bit)
Slots	1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 1 x PCIe 5.0 x4 M.2 Connector 2 x M.2 Socket, supports type 2280 SATA3 6.0 Gb/s PCIe Gen4x4 (64 Gb/s) modes
Hard Drive	Up to 2 x 2.5inch SATA Solid State Drive or HDD Up to 3 x M.2 Socket SSD Solid State Drive RAID 0, RAID 1, and RAID 10 support
Audio	Hi-Fi Audio with DTS:X® Ultra ALC4080 CODEC
Peripheral Interfaces	Front / Top Ports: USB 3.2 Gen1 Type-A Ports ; USB Type C Port; 2x Audio Jack Motherboard Rear Ports: 1 x DisplayPort and 1 x HDMI port 1 x Rear USB 3.2 Gen 2 Type-C® with DisplayPort™ Alternate Mode 2 x USB 3.2 Gen 2 Type-A ports (red) 2 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port; 2 x SMA antenna connectors (2T2R) 1 x Q-Flash Plus button 2 x audio jacks
LAN Support	Intel® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) 802.11ac WiFi Module Dual-Band (2.4/5 GHz) ; I Bluetooth 5.3
Chassis Type Dimension Power Supply	Mini ITX Chassis with Dual Side Panel Doors design (L)426*(W)170*(H)325mm Standard: 700 WATTS High Efficiency 80Plus Gold Power Supply Optional: 1000 WATTS High Efficiency 80Plus Gold Power Supply
System Cooling	2 x 120mm RGB Cooling Fan (Front) 2 x 120mm RGB Cooling Fan (Top) Supports 240mm AIO RGB Liquid Cooling System
Standard Warranty and Service Offerings	Service Offerings 3-Year Limited Parts Warranty & Technical Support Policy; 1-Year Next Business Day On-site Service Optional 3 Years Next Business Day on-site



XITRIX COMPUTER CORPORATION
23 Detroit St. Cubao, Quezon City
Tel: (632) 721 9999 Email: sales@xitrix.net
Fax: (632) 570 8034 Support@xitrix.net

