



OptoFrame™ X5

Ultimate workstation platform to power next gen compute-intensive professional workloads

- Supports 4th Gen Intel® Xeon® W-3400 and W-2400 Processors ; Up to 56Cores and 112 Threads
- Up to 2TB ECC DDR5 System Memory
- Up to 5 Hot Swappable SATA / SAS Hard Drive
- Supports RAID Configuration
- Up to 48GB nVidia Quadro RTX Professional Graphic Card
- Dual 10 Gigabit LAN and One 2.5 Gigabit LAN



MODEL OptoFrame™ X3

Processors	Supports 4th Gen Intel® Xeon® W-3400 and W-2400 Processors ; Up to 56Cores and 112 Threads
Core Chipset	Intel® W790 Workstation chipset
Operating System	Microsoft® Windows® 11 Professional; 64bit version
System Memory	8 x DDR5 DIMM Slots; Up to 2TB DDR5 System Memory Quad Channel DDR5 Memory Technology Supports DDR5 ECC, buffered memory (RDIMM/ RDIMM-3DS/ RDIMM-9x4) up to 6800+(OC)
Optional Graphics	Support for Dual PCI Express® x16 Gen 4 graphics cards NVIDIA RTX Professional Graphic Card
M.2 Slots	- 1 x M.2 Socket supports type 2230/2242/2260/2280 PCIe Gen5x4 (128 Gb/s) mode - 2 x M.2 Sockets support type 2260/2280 PCIe Gen5x4 (128 Gb/s) mode - 1 x M.2 Socket supports type 2260/2280 PCIe Gen5x4 (128 Gb/s) mode
Hard Drive	SATA 6Gb/s connectors Support Raid 0, 1, 5, 10 Optional 8 Port SATA / SAS 12Gb/s RAID Card W/ Support for (RAID 0, 1, 5, 6,10, 50, JBOD) Standard Fixed Hard Drive Cage; Upgradeable to 5 Hotswappable 3.5inch Hard Drives or 2.5inch SSD Drives
I/O Ports	- 2 x Antenna Ports, 1 x Optical SPDIF Out Port - 2 x USB4 Type-C Ports 40Gbps - 2 x USB 3.2 Gen2 Type-A Ports (10 Gb/s) - 4 x USB 3.2 Gen1 Ports - 3 x RJ-45 LAN Ports - 1 x BIOS Button - 1 x Line Out Jack (Gold Audio Jack) - 1 x Microphone Input Jack (Gold Audio Jack)
Expansion Capabilities	4 x PCIe 5.0 x16 Slots (PCIE1/PCIE3 at x16; PCIE2/PCIE5 at x8)
LAN Support	802.11ax Wi-Fi 6E Module Supports Dual-Band 2x2 with extended 6GHz band support 2 x 10 Gigabit LAN 100/1000/2500/5000/10000 Mb/s 1 x 2.5 Gigabit LAN 10/100/1000/2500 Mb/s
Chassis	Industrial Grade Pedestal Server Chassis convertible to 4U Rack-Mount Server Supports Pedestal and 4U Rack Chassis Product Dimensions (DxWxH; Chassis Only): 596x 430 x 174.8mm
Chassis Fan	• 80 x 25mm PWM rear fan x 2, 4500RPM • 80 x 25mm PWM rear fan x 2 (optional), 4200RPM • 80 x 25mm PWM rear fan x 2 (optional), 4500RPM
Power Supply	1050Watts High Efficiency 80Plus Gold Power Supply Supports SLI & Crossfire Multi-GPU VGA card (Single CPU Configuration) or 1,600w High Efficiency 80Plus Gold Rated Power Supply Supports SLI & Crossfire Multi-GPU VGA card (Multi CPU Configuration)
Standard Warranty and Service Offerings	Service Offerings 3-Year Limited Parts Warranty & Technical Support Policy; 1-Year Next Business Day On-site Service Optional 3 Years Next Business Day on-site



XITRIX COMPUTER CORPORATION
23 Detroit St. Cubao, Quezon City
Tel: (632) 721 9999 Email: sales@xitrix.net
Fax: (632) 570 8034 Support@xitrix.net

