



Xitrix 24-inch Monitor

Productivity Monitor

- **Stunning resolution**: Get amazing clarity with FHD resolution (1920 x 1080) for exceptional viewing on an expansive 24-inch screen.
- **Seamless setup**: Experience virtually seamless viewing across a dual- or multiple-monitor setup thanks to ultrathin bezel
- Energy Star: This eco-friendly monitor is designed for sustainable productivity. Super-energy-efficient design delivers a new level of power savings
- Peace of mind included: Relax knowing that your monitor comes with a 3-year Limited Hardware Warranty.

Xitrix 24 inch Professional LED Monitor

Technical Specification Model XPN-WFP2413 Size 23.8" Panel Full HD VA Panel Display scale 16:9 Backlight ELED edge Type Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178°, V:178° (CR>10) Brightness Typ:300cd/m²	
Size 23.8" Panel Full HD VA Panel Display scale 16:9 Backlight ELED edge Type Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Panel Full HD VA Panel Display scale 16:9 Backlight ELED edge Type Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Display scale 16:9 Backlight ELED edge Type Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Backlight ELED edge Type Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Maximum resolution 1920×1080; 60Hz / 75Hz Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Pixel Pitch 0.2745 (H) x 0.24455 (V) Viewing angle H:178º,V:178º (CR>10) Brightness Typ:300cd/m2	
Viewing angleH:178º,V:178º (CR>10)BrightnessTyp:300cd/m2	
Brightness Typ:300cd/m2	
Contrast ratio Typ:3000 : 1; Dynamic Contrast	
Response time 5ms	
Display Colors 16.7m	
Color Gamut(NTSC) Typ:72%	
HDMI 2.0 x 1 (1920*1080@75Hz)	
Input Interface VGA x 1 (1920*1080@60Hz)	
AUDIO IN x 1 (with speaker); Earphone Out x 1	
Non Flash Screen Support (DC Adjust)	
Blue-light filtering Support Blue-light filtering	
Vesa Support 100mm×100mm VESA Standard	
Tiltable -5° ~ 15°	
product size(without base) 540.6*319.8*42.0mm	
product size(with base) 540.6*416.0*195.0mm	
Weight Gross weight 4.1kg; Net weight(with stand) 2.8kg	
Power Management	
Power input DC 12V/3A	
Working consumption ≤36W	
Standby consumption ≤0.5W	
Audio power(Optional) 2*2W	
Safety	
Withstand voltage strength ≤10mA @3.0KV AC/60S	
Leakage current ≤3.5mA @264V AC/60S	
Earthing protective resistance ≤100mΩ	
Working condition Temperature: 5°C~40°C humidity: 10%~85% atmosphere: 86KPa~104KPa	
Storage condition Temperature: -20°C~55°C humidity: 5%~95% atmosphere: 86kPa~104kPa	
Warranty 3 Years Standard Warranty	



XITRIX COMPUTER CORPORATION

23 Detroit St. Cubao, Quezon City
Tel: (632) 721 9999 Email: sales@xitrix.net
Fax: (632) 570 8034 Support@xitrix.net



