



## Xitrix 24-inch Monitor

### All Around Productivity Monitor

- **Stunning resolution:** Get amazing clarity with FHD resolution (1920 x 1080) for exceptional viewing on an expansive 24-inch screen.
- **Seamless setup:** Experience virtually seamless viewing across a dual- or multiple-monitor setup thanks to Borderless bezel
- **Multiple Ports:** HDMI 2.0 port provide up to 100Hz refresh rate, refining picture clarity in all action-packed gaming sequences and graphic design projects. Audio In and a Headphone Jack provide diverse audio options. VGA Port provides legacy device support
- **Energy Star:** This eco-friendly monitor is designed for sustainable productivity. Super-energy-efficient design delivers a new level of power savings
- **Height Adjustable:** Tilt, swivel, pivot and adjust the height of your monitor for extra comfort during work
- **Peace of mind included:** Relax knowing that your monitor comes with a 3-year Limited Hardware Warranty.

### Xitrix 24 Inch Professional IPS LED Monitor

Technical Specification	
Model	XPN-WFP2415-100v5
Size	23.8"
Panel	Full HD IPS Panel
Display scale	16:9
Backlight	ELED edge Type
Maximum resolution	1920×1080; 75Hz
Pixel Pitch	0.2745 mm x 0.2745 mm
Viewing angle	H:178°,V:178° (CR>10)
Brightness	Typ:300cd/m2
Contrast ratio	Typ:1000 : 1; Dynamic Contrast
Response time	5ms
Display Colors	16.7m
Color Gamut(NTSC)	Typ:72%
Input Interface	HDMI 2.0 x 1 (1920*1080@100Hz) VGA x 1 (1920*1080@60-75Hz) AUDIO IN x 1 (with speaker) ; Earphone Out x 1
Non Flash Screen	Support (DC Adjust)
Blue-light filtering	Support Blue-light filtering
Vesa Support	100mm×100mm VESA Standard
Tiltable	Full Height Adjustable Screen Rotate Monitor Stand Rotation Angle (vertical-horizontal): -90°±3°/+90°±3° Tilt Angle: 5±3°/-20±3° Height Adjustment: 130±4mm Swivel Angle (left-right): -45°±3°/+45°±3° VESA Mounting Interface : 100 x 100 mm
Mechanical	
product size(without base)	540.6*319.8*42.0mm
product size(with base)	540.6*416.0*195.0mm
Weight	Gross weight 4.1kg; Net weight(with stand) 2.8kg
<b>Power Management</b>	
Power input	Built in Power
Working consumption	≤36W
Standby consumption	≤0.5W
Audio power(Optional)	2*2W Speaker
<b>Safety</b>	
Withstand voltage strength	≤10mA @3.0KV AC/60S
Leakage current	≤3.5mA @264V AC/60S
Earthing protective resistance	≤100mΩ
Working condition	Temperature : 5°C~40°C humidity : 10%~85%atmosphere : 86KPa~104KPa
Storage condition	Temperature : -20°C~55°C humidity : 5%~95%atmosphere : 86KPa~104kPa
Warranty	3 Years Standard Warranty

XITRIX COMPUTER CORPORATION  
23 Detroit St. Cubao, Quezon City  
Tel: (632) 721 9999 Email: sales@xitrix.net  
Fax: (632) 570 8034 Support@xitrix.net

