

Harlequin® HydroClear

SEWAGE TREATMENT PLANT

HydroClear HC20 Wastewater Treatment Plant

HydroClear represents significant progress for the domestic wastewater treatment industry.

Contemporary design engineering and analysis software and state-of-the-art manufacturing facilities combine to create this unique product which dominates the sewage treatment plant market with class-leading pollutant removal level of 97%.



Standard Features:

- ◆ Tank body moulded in one piece from durable medium density polyethylene material
- ◆ 110mm inlet and outlet connections
- ◆ Integrated lifting eyes for ease of handling and installation
- ◆ Fully secured 450mm pedestrian duty manhole covers comply with statutory regulations
- ◆ Adjustable turrets allowing for shallower invert levels
- ◆ Above ground air blower housing delivers more reliable and efficient operation, and allows easy access for maintenance
- ◆ Easy access to the bubble diffuser within the tank
- ◆ Virtually silent operation
- ◆ Cost effective installation
- ◆ 24 month service period reduces operating costs
- ◆ HydroClear owners can determine their own de-sludge intervals giving potential cost savings
- ◆ Mechanically reliable with no moving parts or electrics within the tank
- ◆ Certified to EN12566-3

Harlequin® HydroClear

SEWAGE TREATMENT PLANT

HydroClear HC20 Wastewater Treatment Plant

Optional Equipment:

- ◆ Air blower function alarm
- ◆ Pumped outlet
- ◆ 300mm manhole riser(s). Max 3 risers on a gravity tank or 2 risers on a pumped outlet⁺
⁺ *Maximum invert level 2m. Use 1200mm concrete rings to achieve inverts below max. number of risers.*

Technical Data:

Treatment Efficiency		Efficiency	Effluent	
		COD	91.2%	59 mg/l
		BOD ₅	96.6%	11 mg/l
		NH ₄ -N	85.8%	4.5 mg/l
		SS	94.7%	19 mg/l
Nominal hydraulic daily load	4,000Litres / day			
Nominal organic daily load	1,200g BODs / day			
Inhabitants served	13 - 20			
Desludging interval	6 months *			
Electrical consumption	2.7 kWh/d			
Power requirements	230V 112W 1A (start-up current)			
Volumes (at operational height)	Primary settlement – 3700 Litres Aeration chamber – 2400 Litres Final settlement –2280 Litres			
Overall dimensions	L 5680 W 1400 H 2560 mm			
Standard inlet depth	1090 mm			
Standard outlet depth	1140 mm			
Depth from invert to base	1470 mm			
Depth from base to ground	2560 mm			
Pipe diameter	110 mm			
Net Weight	700 kg			

* de-sludge interval up to 6 months depending on the number of inhabitants

Issued By:

Harlequin Manufacturing Limited
21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB
T: +44 (0)28 9261 1077
W: www.harlequin-mfg.com
E: info@harlequin-mfg.com