

*Capitalizes on the advantages of off-site construction, controlled environment craftsmanship, and cost efficiencies, while delivering an outstanding wall finish*

12/11/2020

## TECHNICAL DATA

TEST METHOD	REPORT	TEST CRITERIA	TEST RESULTS
ASTM E84	<b>Surface Burning</b>	< 25 Flame Spread < 450 Smoke Developed	0      Class A 2.4      Class A
ASTM D2486	<b>Scrub Resistance</b>	10,000 cycles	Pass
ASTM D3960	<b>VOC</b> **This product complies with South Coast AQMD (Rule 1113) VOC emission standards for architectural coatings.		ZERO VOC
ASTM D3273	<b>Mold/Mildew Resistance</b>	No growth at 28 days	No growth
ASTM D3363	<b>Pencil Hardness</b>	6B – 6H	5H
ASTM D3359	<b>Adhesion by Tape Test</b>	No peeling or removal	5A
ASTM D1308	<b>Chemical Resistance</b>		High

## FEATURES

## BENEFITS

<b>Controlled environment made</b>	Highest quality possible, less room for error, consistent
<b>Off-site construction</b>	Reduces construction site congestion
<b>Modular nature</b>	Easy on-site installation
<b>Finished product</b>	Shorter construction schedule; No on-site mess
<b>Hand-crafted and hand applied</b>	Enables highly customizable designs and finishes
<b>Lightweight</b>	Quick and easy installation

*Capitalizes on the advantages of off-site construction, controlled environment craftsmanship, and cost efficiencies, while delivering an outstanding wall finish*

12/11/2020

---

## DESCRIPTION

- Decorative finish panels that are finished by hand using the namesake materials that describe them (Fresco Concrete, Fresco Mica, etc.)
- Most common substrate is MDF, either ¼", ½" and ¾"
- Maximum panel size is 4'x10'
- Top surface of panel is coated with a flexible, decorative plaster coating at a thickness of 1-5mm
- All finishes are sealed for maximum protection and durability
- Can be highly customized to suit the individual client
- Affords compressed construction schedules and helps minimize delays
- Lower cost than on-site traditional wet application
- Lightweight and easily installed
- All panels are provided with finished edges and ready for hanging
- Suitable for any design application

---

## INSTALLATION

- Z-clips, construction adhesive, screws, or standoffs
- Fast on-site installation
- No specialist installation required

---

## CARE & CLEANING

- Easily cleaned with water and cloth
- Stains and mars can be removed with a white Magic Eraser
- Always do a small test in an inconspicuous area if possible.

---

## WARRANTY

- All products are warranted against defects including peeling, excessive cracking, flaking or corrosion simply as result of defects in materials or workmanship for a period of ten (10) years from the original date of purchase. Some of the above issues may occur if the product is installed in an environment or fashion not recommended by StudioÄix. Be sure to contact us first should you have any questions or concerns about whether the environment and/or fashion that you intend to install within is suitable and can be warranted.