# SAFETY DATA SHEET

## FOR INDUSTRIAL USE ONLY

## CP-1500

## Section 1. Product and company identification

GHS product identifier

CP-1500

MSDS Number

SDS0140

Product type

Adhesive

Material uses

Wood Adhesives, Composites, Laminates or Related Board Products

Supplier

: Spectrum Adhesives, Inc.

5611 Universal Dr. Memphis, TN 38118

Contact person

rthomas@spectrumadhesives.com

Telephone

For additional health and safety or regulatory information, call

(901) 795-1943

Emergency telephone number

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

## Section 2. Hazards identification

Classification of the substance or

mixture

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

**COMBUSTIBLE DUSTS** 

GHS label elements

Hazard pictograms

EE

Signal word

Danger

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

May form combustible dust concentrations in air.

#### **Precautionary statements**

Version: 7.0 /

Date of issue/Date of revision:

06/25/2015

Date of previous issue:

Page: 2/15

General

Not applicable.

Prevention

Wear protective gloves.
Wear eye or face protection.

Wash hands thoroughly after handling.

Response

IF ON SKIN:

Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage

Not applicable.

Disposal

Not applicable.

Other hazards which do not result in classification

Combustible dust when finely divided and suspended in air. Fine dust clouds may form explosive mixtures with air. Product can explode if

dust cloud is formed and ignited.

Minimize airborne dust. Eliminate all fire/ignition sources including static discharges near product/package. Prevent dust accumulation. Refer to Handling Section 7 of the MSDS for more information.

Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

# Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Ingredient name	% by weight	CAS number	
Sodium Silicate (Na2SiO3)	10 - 15	6834-92-0	
Calcium Oxide	5 - 10	1305-78-8	
Trisodium Phosphate	5 - 10	7601-54-9	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

SDS - CP-1500 Page: 3/15

Eye contact Get medical attention immediately. Call a poison center or physician.

> Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be

treated promptly by a physician.

Inhalation Get medical attention immediately. Call a poison center or physician.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer

should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be

kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first aid personnel No action shall be taken involving any personal risk or without

> suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly

with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

Skin contact

Ingestion

Suitable extinguishing media Use water spray or mist, dry chemical, foam or CO2.

Unsuitable extinguishing media Do not use water jet.

Version: 7.0 Date of issue/Date of revision: 06/25/2015 Date of previous issue: 04/20/2015 SDS - CP-1500 Page: 4/15

Specific hazards arising from the chemical

Hazardous thermal decomposition products Combustible solid that burns. Fine dust clouds may form explosive mixtures with air.

Decomposition products may include the following materials: phosphorus oxides

metal oxide/oxides

Special protective actions for firefighters

Special protective equipment for

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark

fire-fighters

Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). The ATEX Directive defines combustible powders as less than 500 microns in diameter. When processed with flammable liquids/vapors/mists, ignitable (hybrid) mixtures may be formed with combustible dusts. Ignitable mixtures will increase the rate of explosion pressure rise and the MIE will be lower than the pure dust in

air mixture. The Lower Explosive Limit (LEL) of the vapor/dust mixture will be lower than the individual LELs for the vapors/mists or

dusts. See NFPA 77 for additional guidance.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel

> suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Minimize airborne dust and eliminate all fire/ignition sources. Clean up spill as soon as possible using procedures described below. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on

appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of For emergency responders

any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and material for containment and cleaning up

Small spill Move containers from spill area. Do not use air hoses for cleaning.

> Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed

waste disposal contractor.

Large spill Move containers from spill area. Approach release from upwind.

Version: 7.0 Date of issue/Date of revision: 06/25/2015 Date of previous issue: 04/20/2015 Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see section 8 of SDS). Do not get in eyes or on skin or clothing. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### COMBUSTIBLE DUST HANDLING PROCEDURES:

Combustible dusts at sufficient concentrations can form explosive mixtures with air. High dust concentrations should be avoided. Follow US NFPA Standard 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids," UK HSE Guidance HSG 103, approved Codes of Practice (ACOPS) established for Explosive Atmospheres under the ATEX Directive 1999/92/EC for worker protection and ATEX Directive 94/9/EC that regulates equipment and protection systems used in potentially explosive atmospheres or other national guidance on safe handling of combustible dusts. Train workers in the recognition and prevention of hazards associated with combustible dust in the plant.

Minimize airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. Use continuous suction at points of dust generation to capture and minimize the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimize the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.

Control sources of static electricity. This product or the package itself

Date of issue/Date of revision: 06/25/2015 Date of previous issue: 04/20/2015

can accumulate static charges, and static discharge can be a source of ignition. Solids handling systems must be designed in accordance with applicable NFPA standards (including 654 and 77) and other national guidance. Do not empty directly into flammable solvents or in the presence of flammable vapors. The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.

### Advice on general occupational hygiene

SDS - CP-1500

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep away from heat, hot surfaces, sparks and flame. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits *
Sodium Silicate (Na2SiO3)	ACGIH TLV () Time Weighted Average (TWA) 2 mg/m3
Calcium Oxide	ACGIH TLV (1994-09-01) Time Weighted Average (TWA) 2 mg/m3 OSHA PEL (1993-06-30) Time Weighted Average (TWA) 5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3
Trisodium Phosphate	AIHA WEEL (1999-01-01) Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 5 mg/m3  ACGIH TLV () Particles (Insoluble or Poorly Soluble) Not Otherwise Specified  Time Weighted Average (TWA) 10 mg/m3 Form: inhalable

Version: 7.0 Date of issue/Date of revision: 06/25/2015

Date of previous issue:

particulate

Time Weighted Average (TWA) 3 mg/m3 Form: respirable OSHA PEL 1989 Vacated () Particles (Insoluble or Poorly Soluble) Not Otherwise Specified

Time Weighted Average (TWA) 5 mg/m3 Form: respirable particulate Time Weighted Average (TWA) 15 mg/m3 Form: total dust

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., For PPE selection see National Fire Protection Association (NFPA) 2113,

Version: 7.0

Date of issue/Date of revision: 06/25/2015

Date of previous issue: 04/20/2015

Standard on Selection, Care, Use and Maintenance of Flame-Resistant

Garments for Protection of Industrial Personnel Against Flash Fire.

Appropriate footwear and any additional skin protection measures Other skin protection

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Use a properly fitted, particulate filter respirator complying with an Respiratory protection

approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

# Section 9. Physical and chemical properties

#### Appearance

Physical state

Solid

Color

Tan.

Odor

Little or none

Odor threshold

Not available

pH

Not applicable.

Melting point/ Freezing point

. Not applicable.

**Boiling** point

Not applicable.

Flash point

Not determined

**Burning time Burning** rate **Evaporation rate** 

Not available Not available

Not applicable.

Flammability (solid, gas)

Not available

Lower and upper explosive

Lower: Not applicable.

(flammable) limits

Upper: Not applicable.

Vapor pressure

Not applicable.

Vapor density

Not applicable.

Relative density

0.70

Solubility

Not available

Solubility in water

Soluble

Partition coefficient: n-

octanol/water

Not available

Auto-ignition temperature

Not applicable.

Decomposition temperature

Not available

SADT

Not available : Dynamic: Not available

Viscosity

Kinematic: Not available

Date of issue/Date of revision: 06/25/2015

Date of previous issue: 04/20/2015

#### Other information

The SDS is not to be used as a specification sheet. For Specific technical information on the product listed above, a sales specification sheet should be obtained from your representative.

# Section 10. Stability and reactivity

Reactivity

Stable under normal conditions.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid

Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers

and equipment before transferring material. Prevent dust

accumulation. See Section 7 Handling.

Incompatible materials

Reactive or incompatible with the following materials:

oxidizing materials

acids

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Result	Species	Dose	Exposure
LD50 Oral	Rat	1,153 mg/kg	-
LD50 Oral	Rat	> 2,000 mg/kg	- ^
LD50 Dermal	Rabbit	> 2,500 mg/kg	-
LD50 Oral	Rat	6,500 mg/kg	-
	LD50 Oral LD50 Oral LD50 Dermal	LD50 Oral Rat  LD50 Oral Rat  LD50 Dermal Rabbit	LD50 Oral         Rat         1,153 mg/kg           LD50 Oral         Rat         > 2,000 mg/kg           LD50 Dermal         Rabbit         > 2,500 mg/kg

Conclusion/Summary

Not available

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Sodium Silicate (Na2SiO3)	Skin - Severe irritant	Human		24 hrs	-
	Skin -	Rabbit		24 hrs	-

Version: 7.0

Date of issue/Date of revision:

06/25/2015

Date of previous issue:

Severe irritant

Conclusion/Summary

Skin eyes

Not available Not available Not available

Respiratory

Sensitization

Conclusion/Summary

Skin Respiratory Not available Not available

Mutagenicity

Conclusion/Summary

Not available

Carcinogenicity

Conclusion/Summary

Not available

Reproductive toxicity

Conclusion/Summary

Not available

**Teratogenicity** 

Conclusion/Summary

Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium Oxide	Category 3		Respiratory tract irritation
Trisodium Phosphate	Category 3	72	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available

#### **Aspiration hazard**

Not available

Information on the likely routes of

Not available

#### Potential acute health effects

Eye contact

Causes serious eye damage.

Inhalation

May give off gas, vapor or dust that is very irritating or corrosive to

the respiratory system.

Skin contact

Causes skin irritation.

Ingestion

May cause burns to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics

Version: 7.0

Date of issue/Date of revision: 06/25/2015

Date of previous issue: 04/20/2015

Eye contact

Adverse symptoms may include the following:

pain

watering redness

Inhalation

No specific data.

Skin contact

Adverse symptoms may include the following:

pain of irritation

redness

blistering may occur

Ingestion

Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

### Short term exposure

Potential immediate effects

Not available

Potential delayed effects

Not available

#### Long term exposure

Potential immediate effects

Not available

Potential delayed effects

Not available

#### Potential chronic health effects

Conclusion/Summary

Not available

General

No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Carcinogenicity Mutagenicity **Teratogenicity** 

No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

**Developmental effects** Fertility effects

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value	
Oral	9,363.4 mg/kg	
Route	ATE value	
Dermal	284,465.8 mg/kg	

# Section 12. Ecological information

#### Toxicity

Product/ingredient name	Result	Species	Exposure
disodium metasilicate			
	Acute LC50 2,320 mg/l Fresh water	Fish - Western mosquitofish	96 h

Conclusion/Summary

Not available

Version: 7.0

Date of issue/Date of revision: 06/25/2015

Date of previous issue:

#### Persistence/degradability

Conclusion/Summary

Not available

#### Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential	
Calcium Oxide		2.34	low	

#### Mobility in soil

Soil/water partition coefficient

Not available

(KOC)

Other adverse effects

No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

### International transport regulations

Regulatory UN/NA information number

Classes/\*PG

Reportable

Quantity (RQ)

**CFR** 

Non-regulated

Proper shipping name

TDG

Non-regulated

**IMO/IMDG** 

Non-regulated

IATA (Cargo)

Non-regulated

Version: 7.0

Date of issue/Date of revision:

06/25/2015

Date of previous issue:

\*PG: Packing group

Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons

transporting the product know what to do in the event of an accident

or spillage.'

# Section 15. Regulatory information

#### **United States**

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not

listed

United States - TSCA 5(e) - Substances consent order: Not listed

California Prop. 65:

WARNING: This product contains a chemical known to the State of

California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Distillates (petroleum), solvent- dewaxed heavy paraffinic A complex combination of hydrocarbons obtained by removal of normal paraff	Yes.	No.	No.	No.

United States inventory (TSCA:

All components are listed or exempted.

8b)

<u>Canada</u>

WHMIS (Canada)

Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2B: Material causing other toxic effects (Toxic).

Class E: Corrosive material

Canadian lists

Canadian NPRI

None required.

**CEPA Toxic substances** 

None required.

International regulations

**International lists** 

Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Version: 7.0

Date of issue/Date of revision:

06/25/2015

Date of previous issue:

New Zealand Inventory (NZIoC): Not determined.

Philippines inventory (PICCS): All components are listed or exempted.

United States inventory (TSCA 8b): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

## Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Health	*	3
Flammability		3
Physical hazards	A LIGHT THE	0
		10

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

Not applicable.

statements

**History** 

Date of printing

Date of issue/Date of revision

Date of previous issue

Version

Prepared by Key to abbreviations 02/13/2019

06/25/2015 04/20/2015

7.0

Product Safety Stewardship ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

References

: Not available

#### Notice to reader

The information provided herein was believed by

be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by are subject to terms and conditions of sale.

MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY except that the product shall conform to specifications. Nothing contained herein constitutes an offer for the sale of any product.

Version: 7.0

Date of issue/Date of revision:

06/25/2015

Date of previous issue:

Version: 7.0 Date of issue/Date of revision: 06/25/2015