

Auxiliaries

HAMR PREPSOLVE Degreaser

Product Description



HAMR PREPSOLVE is particularly well suited for removing grease, oils, wax and silicone prior to the application of HAMR primer and for the pre-treatment of plastic surfaces.

Technical Characteristics

Colour: transparent Shelf life: 48 months at 25°C

Pre-treatment

Do not use the cleaners on solvent-sensitive or thermoplastic substrates.

	<p>Mixing Ratio</p>	<p>This product is ready for use</p> <p>Soak a clean and dry lint-free cloth with HAMR PREPSOLVE</p> <p>Degrease small areas of approximately 0.5 m² of the surface to be painted and wipe these areas immediately afterwards with a dry cloth of the same quality.</p> <p>HAMR PREPSOLVE should not dry on the surface being treated.</p> <p>Attention: Some 1K primers/basecoats may suffer surface etching from the use of PREPSOLVE. In this case, ensure a good flash-off of the substrate before going on with the repair so that no solvents will be trapped in the new paint system. In extreme cases, remove the 1K primer/basecoat before applying the new paint system, or flat with P800-1000 grade sandpaper for refining refinish.</p> <p>As specified in the HAMR refinishing processes.</p>
	<p>Application</p>	
<p>Further Treatment</p>		

The products are suitable for professional use only. The data contained in this publication are based on our current knowledge and experience. You can obtain the latest version of technical data sheet directly from your supplier.

HAMR Coatings Pty Ltd. Australia. Tel (03 8797 5515) HAMRCOATINGS.COM ISSUE 15/10/2021 This supersedes all older data sheets.