

# OUTDOOR TAPE 12V

8011, 8051, 8101

# WAC


## LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_



### PRODUCT DESCRIPTION

Flexible tape light with UV stabilized silicone seals that protect against water and dusts.

### FEATURES

- Conveniently adapts into existing 12V system
- IP 68 rated for submersible up to 5 feet
- May be tied into any 12V landscape lighting system
- Maximum of 40 ft per run to stay within 5 amps
- Flexible linear lights maybe cut to desired length at the end of the run
- Various lengths may be joined together with IP68 rated connectors
- UV-stabilized silicone seals and protects the tape sections
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

### SPECIFICATIONS

**Input:** 9-15VAC (Transformer is required)  
**Power:** 2W / 2.1VA  
**Brightness:** 115 lm  
**CRI:** 85  
**Rated Life:** 60,000 hours  
**Operating Temp:** -40°F(-40°C) to 122°F(50°C)  
 at relative humidity 95%

### ORDERING NUMBER

		Color Temp		Finish
<b>8011</b>	1 foot	<b>27</b>	2700K	<b>BK</b> Black tape color
<b>8051</b>	5 feet		3000K	
<b>8101</b>	10 feet			

\_\_\_\_\_ - \_\_\_\_\_ **BK**

Example: **8011-30BK**

waclighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760

# OUTDOOR TAPE 12V ACCESSORIES

8011, 8051, 8101

# WAC

## LANDSCAPE LIGHTING

Clear channel



**LED-TO24-CH5**

5 feet

Includes mounting hardware

End cap



**LED-TO24-EC**

Surface mounting clip



**LED-TO24-C1**

Secures on both edges  
(10 Qty)

Edge mounting clip



**LED-TO24-C2**

Secures on one edge  
(10 Qty)

Invisible clip



**LED-TO24-C3**

Spring clip secures  
beneath tape (10 Qty)

Lead wire with 5A fuse  
40 ft max tape run



Protects tape sections  
from over current

**8000-06BK**

6 feet

**8000-10BK**

10 feet

Joiner Cable - Short



**8001-6BK**

6 inch

**8001-12BK**

1 foot

Joiner Cable - Long



**8001-72BK**

6 feet

**8001-120BK**

10 feet

4 Way "X" Connector



**8003-BK**

3 Way "Y" Connector



**8002-BK**

### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed  
See transformer spec sheet for details and its accessories

**9075-TRN-SS**

75W Max

**9150-TRN-SS**

150W Max

**9300-TRN-SS**

300W Max

**9600-TRN-SS**

600W Max



waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

# OUTDOOR TAPE 12V ACCESSORIES

8011, 8051, 8101

# WAC

## LANDSCAPE LIGHTING

### TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
<b>8011</b> <b>8051</b> <b>8101</b>		<i>Diva</i>	<i>DVLV-600</i>	<i>600W</i>	<i>33% - 100%</i>	<i>Output maxes at 50% dimming level</i>
	<i>Lutron</i>	<i>Skylark</i>	<i>SLV-600P</i>	<i>600W</i>	<i>28% - 100%</i>	<i>Output maxes at 50% dimming level</i>
		<i>Skylark</i>	<i>S-10P</i>	<i>1000W</i>		<i>Not recommended</i>

\*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760