4" Low Voltage

New Construction Non-IC Housing

Model & Product



Example: HR-8402E

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available with a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Integral electronic transformer
- J-Box and transformer accessible through ceiling
- Advanced auto-reset, soft start and short circuit protection features
- Supplied thermal protector protects against over-lamping
- Transformer included
- 5 year warranty

SPECIFICATIONS

Construction:	20 gauge galvanized steel
Power:	50W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Halogen
Mounting:	Supplied with hanger bars, adjustable from 15"-242" to accommodate various joist construction and grid sizes.
Cut Out:	4 9/16"
Ceiling Thickness:	3/4"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Non IC


Fixture Type:

Catalog Number:

Project:

Location:





4" Low Voltage

Adjustable Step Baffle Trim

Model & Light Source	Lumens	Finish
HR-8411 Halogen MR16 HR-8411LED LED MR16		WT/WT White/White

Example: HR-8411-WT/WT

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	20 gauge steel
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated: White/White
Standards:	UL, cUL, Damp Location Listed

Catalog Number:


Project:

Location:



FINISHES:





4" Low Voltage

Die-Cast Adjustable Step Baffle Trim

Model	ጲ	l iøht	Source	

Model & Light Source	Lumens	Finish
HR-D411 Halogen MR16 HR-D411LED LED MR16		WT/WT White/White

Example: HR-D411-WT/WT

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated: White/White
Standards:	UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:


Project:

Location:



FINISHES:





4" Low Voltage

Die-Cast Adjustable Specular Square Trim

Model & Light Source	Lumens
HP D/12 S Halogon MP16	

HR-D412-S Halogen MR16	SC/BN Specular
HR-D412LED-S LED MR16	Clear/Brushed Nickel
	SC/WT Specular
	Clear/White

Finish

Example: HR-D412-S-SC/BN

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	Halogen MR16, LED MR16
Finish:	Electrostatically Powder Coated:Specular Clear/White, Electrostatically Powder Coated::Specular Clear/Brushed Nickel
Standards:	UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:

Project:


Location:



FINISHES:

C

Specular	Specular Cl
lear/White	ear/Brushe
	d Nickel



4" Low Voltage

Die-Cast Adjustable Specular Round Trim

Model & Light Source	Lumens	Finish
HR-D412 Halogen MR16 HR-D412LED LED MR16		SC/B Clear/Bru SC/W

าร	FINISN
	SC/BN Specular
	Clear/Brushed Nickel
	SC/WT Specular
	Clear/White

Example: HR-D412-SC/BN

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	Halogen MR16, LED MR16
Finish:	Electrostatically Powder Coated:Specular Clear/White, Electrostatically Powder Coated::Specular Clear/Brushed Nickel
Standards:	UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:


Project:

Location:



FINISHES:

Specular Clear/White	Specular Cl ear/Brushe
clear/ write	d Nickel



4" Low Voltage

Die-Cast Adjustable Slotted Trim

Model & Light Source	Lumens	Finish
HR-D413 Halogen MR16 HR-D413LED LED MR16		WT White

Example: HR-D413-WT

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated: White
Standards:	UL, cUL, Damp Location Listed

Fixture Type:		


- Catalog Number:
- Project:

Location:



FINISHES:





4" Low Voltage

Die-Cast Adjustable Square Trim

Model & Light Source	Lumens	Finish

Example: HR-D416-BN

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 30° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Brushed Nickel
Standards:	UL, cUL, Damp Location Listed

Fixture Type:


- Catalog Number:
- Project:

Location:



FINISHES:





4" Low Voltage

Die-Cast Gimbal Ring Trim

Model & Light Source	Lumens	Finish
HR-D417 Halogen MR16 HR-D417LED LED MR16		BN Brushed Nickel WT White

Example: HR-D417-BN

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 25° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Brushed Nickel
Standards:	UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:


Project:

Location:



FINISHES:





4" Low Voltage

Die Cast Shower Trim Clear Flat Glass

Model & Light Source	Lumens	Finish
HR-D418-S Halogen MR16 HR-D418LED-S LED MR16		WT White

Example: HR-D418-S-WT

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	LED MR16, Halogen MR16
Finish:	Electrostatically Powder Coated: White
Standards:	UL, cUL, Wet Location Listed

Fixture Type:

Catalog Number:


Project:

Location:



FINISHES:





4" Low Voltage

Die-Cast Adjustable Round Trim

Model & Light Source	Lumens	Finish
HR-D425 Halogen MR16 HR-D425LED LED MR16		WT White

Example: HR-D425-WT

DESCRIPTION

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Center lamp holder allows lamp to be tilted up to 80° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Input:	12 VAC
Light Source:	Halogen MR16, LED MR16
Finish:	Electrostatically Powder Coated: White
Standards:	UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:

Project:

Location:



FINISHES:



