



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

August LED Outdoor Sconce AUGW Series

Features

Ideal use for general lighting in indoor or outdoor residential, commercial, and hospitality applications.
Fixture can be mounted to a standard junction box (not included).

Construction

Stainless steel housing with aluminum die-cast trim and painted in weather resistant powder coating. Back pan is made from 12 gauge stamped aluminum material with matching powder coat finish. Power supply connections must be made inside a junction box (not included).

Finish

Black or Painted Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277VAC / 60Hz.
Minimum starting temp -4° F/-20° C

LED

Integrated LED modules capable of producing:
26W = 1700 delivered lumens
35W = 2200 delivered lumens
40W = 2600 delivered lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 80 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations.
Title 24/J8A Compliant
ADA

Option

Integrated Dusk to Dawn photocell (-PC)

Warranty

5 Year Limited Warranty:

Restrictions apply based on location.

**Specifications and dimensions
subject to change without notice.**

Ordering Information:

| Black | Painted Nickel | LED | Delivered Lumens | Adjustable CCT | H | W | D |
|---------------------|---------------------|-----|------------------|-------------------|-----|--------|--------|
| AUGW0612LAJMV BK | AUGW0612LAJMV NP | 26W | 1700 | 3000K/3500K/4000K | 12" | 5-1/2" | 3-3/4" |
| AUGW0612LAJMV BK-PC | AUGW0612LAJMV NP-PC | 26W | 1700 | 3000K/3500K/4000K | 12" | 5-1/2" | 3-3/4" |
| AUGW0720LAJMV BK | AUGW0720LAJMV NP | 35W | 2200 | 3000K/3500K/4000K | 20" | 7" | 3-3/4" |
| AUGW0720LAJMV BK-PC | AUGW0720LAJMV NP-PC | 35W | 2200 | 3000K/3500K/4000K | 20" | 7" | 3-3/4" |
| AUGW0736LAJMV BK | AUGW0736LAJMV NP | 40W | 2600 | 3000K/3500K/4000K | 36" | 8" | 3-3/4" |
| AUGW0736LAJMV BK-PC | AUGW0736LAJMV NP-PC | 40W | 2600 | 3000K/3500K/4000K | 36" | 8" | 3-3/4" |

