

Delgado LED Linear DLGL Series

Features

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, bath, hallway, kitchen and anywhere general lighting is needed. Fixture mounts to standard junction box (not included). Convienient lift and shift installation.

Construction

Aluminum picture frame construction. Fixture includes tether cords to allow for easy installation. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or White finish.

Diffuser

White acrylic diffuser.

Electrical D1

Input 120 VAC 60 HZ.

Compatible with residential TRIAC and ELV dimming only at 120 VAC.

Electrical D3

Input 120-277 VAC 60 HZ. 1-10V dimming.

LED

Integrated LED modules capable of producing: 34W = 2400 delivered lumens 45W = 3200 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cCSAus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE














Ordering Information:

W I	W [D
6"	S" (1"
6"	ô" ´	1"
6"	ŝ" ´	1"
6"	6"	1"
	6	6" 6"