

| Design | Ву | |
|-----------|----|--|
| F=:- C=14 | | |

Eric Solé

Collection =

Design

| | . (J), |
|---------------|----------------|
| $\overline{}$ | |



| ։ Մա | (P2 |
|---------|-----|
| | |

| | | _ | | | | |
|-----|-----|---|----|----|----|-----|
| Col | ors | & | Εi | ni | sh | ies |

| | 1 |
|-----|---------|
| 1 1 | \\/bi+a |
| | |

Materials =

- Body in painted die-cast aluminum
- Wall support in painted die-cast aluminum


Specifications —

| The second secon | |
|--|-------------------------------|
| Delivered lumens | 1736lm |
| Light output ratio | 59.9lm/W |
| Power consumption | 29W |
| Led type | 25W C.O.B.* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >90 |
| Life expectancy | 50000Hrs |
| Control type | Dimmable 2-Wire** |
| Input Voltage | 120-277V |
| Driver | HATCH - 1 x XTC32-0700P-UNV-I |

^{**}Reverse or forward phase (120v only)

Features & Accessories

Dimensions =



Packaging =

1 Box

1 x 17-13/16" x 9-15/16" x 9-15/16" / 5.29 lbs - 45 cm x 25 cm x 25 cm / 2.4 kg

Light distribution =

Direct/Indirect

Luminaire weight —

3.09 lbs / 1.4 kg

Warranty =

5 year limited warranty