

Design By

BJARKE INGELS GROUP

Collection ==

Design



Colors & Finishes =

1
White

Materials =

- Illuminated tubes in opaque injection molded PMMA
- Canopy in steel and aluminum with powder coated finish

Specifications —


Delivered lumens	4800lm
Light output ratio	73lm/W
Power consumption	66W
Led type	66W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>95
Life expectancy	36000Hrs
Control type	Dimmable**
Input Voltage	24VDC
Driver	Remote power supply (sold separately)

^{*}Integrated light source **With dimmable power supply

Features & Accessories —

- · Patented optical unit
- Flexible tube of light let's you create your own design by changing the spacing

Dimensions =




Light distribution =

Diffused

Luminaire weight —

18.29 lbs / 8.3 kg



Warranty

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

Packaging =

3 Boxes

1 x 32" x 32" x 6-3/8" / 23.59 lbs - 81 cm x 81 cm x 16 cm / 10.7 kg

2 x 6-3/8" x 6" x 5-3/16" / 1.94 lbs - 16 cm x 15 cm x 13 cm / .88 kg

