



GE  
Lighting

### 66864 - LED 6 DC 350mA Plastic

#### GELD6DMV350SL

- ☞ Previous SKU: 901006351U
- ☞ LED 6W DC 350mA - LED Driver, Constant Current, Plastic Housing. Potted, with Leads
- ☞ Current: DC
- ☞ Designed for IP67
- ☞ Reinforced insulation from input to output
- ☞ Small form factor
- ☞ Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal
- ☞ AC Input Fast Start-Up Time
- ☞ 120-277V Input
- ☞ High-efficiency, high Vout range (up to 2-20V)

### GENERAL CHARACTERISTICS

Enclosure Type	Plastic
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	71 °C
Storage Temperature	-10 °C
Color	Black
Primary Application	LED in- and outdoor lighting Architectural lighting Orientation lighting Ambience lighting Task, Table and Floor lighting
Product Technology	LED
CV/CC	CC
CC/CVValue	350 mA
Efficiency	0.7 %
Output Power (W)	6 W
Output Current (A)	0.35 A
Output Voltage[Min]	2 V
Output Voltage[Max]	20 V

### PRODUCT INFORMATION

Product Code	66864
Description	GELD6DMV350SL

### DIMENSIONS

Mount Length	52 mm
Nominal Length	60 mm
Width	45 mm
Height	25 mm

Lead Color	Qty	Exit	Length ( 1 in.)
Black	1	Terminals	220mm
White	1	Terminals	220mm
Red	1	Terminals	220mm

### ELECTRICAL CHARACTERISTICS

Power Factor Correction	Passive
Power Factor %	0.5
Output Current Frequency-Hertz	0 kHz
Supply Current Freq nominal Hz	50 Hz
60 Hz	Input Current Range[Max]
0.12 A	Input Current Range[Min]
0.07 A	Input Voltage Range[Min] (V)
120 V	Input Voltage Range[Max]