ASCOLI TWIN

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (mm): CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): ADA COMPLIANT:

IC RATING:

LAMP

| LIGHT SOURCE: | GU10 |
|--------------------------------|-----------|
| WATTAGE: | 2 x 50W |
| RECOMMENDED LAMP: | 6W Max Ll |
| LAMP INCLUDED: | No |
| MAXIMUM LAMP LENGTH (mm/inch): | 57 |
| LUMINOUS FLUX (Im): | Lamp Dep |
| COLOUR TEMP (K): | Lamp Dep |
| CRI (Ra): | Lamp Dep |
| MACADAM ELLIPSE: | Lamp Dep |
| TILT ADJUSTABLE ANGLE (°): | 90 |
| ROTATION ADJUSTABLE ANGLE (°): | 330 |
| LIFETIME (hrs): | Lamp Dep |
| BEAM ANGLE (°): | Lamp Dep |
| | |

ELECTRICAL


| SWITCHED: | No |
|-----------------------------|----------------|
| DIMMABLE: | Yes |
| DIMMING METHOD: | Lamp Dependent |
| SUPPLY FREQUENCY (Hz): | - |
| DRIVER/BALLAST VOLTAGE (V): | - |
| DRIVER LIFETIME (hrs): | - |
| EFFICACY (Im/W): | Lamp Dependent |

ADDITIONAL INFORMATION:

| SHADE INCLUDED: | - |
|--------------------------|--|
| SHADE/DIFFUSER MATERIAL: | - |
| SHADE/DIFFUSER FINISH | - |
| F MARK: | Suitable for mounting on flammable materials |

Interior cETLus (Class 1) Dry Mains 120V Ceiling & Wall Mount 4" Octagon Box Metal - Aluminium H: 130 W: 350 D: 110 H: 5.12 W: 13.78 D: 4.33 --

4.18 Yes - if installed in compliance with ADA 307.4





CODE: 1286072 FINISH: TEXTURED WHITE



CODE: 1286073 FINISH: BRONZE





CODE: 1286074 FINISH: MATT NICKEL

CODE: 1286118 FINISH: MATT BLACK

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

