## CATENALED

# astro

#### GENERAL

LOCATION: Bathroom
CLASS: cULus (Class 1)

LOCATION RATING: Damp
DRIVER REQUIRED: Mains 120V
INSTALLATION ORIENTATION: Wall Mount

FITTING METHOD: 1/2" Stub Mount & 4" Octagon

MAIN MATERIAL:

DIMENSIONS (mm):

D: 300 Ø: 250

DIMENSIONS (inch):

D: 11.81 Ø: 9.84

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

7.27

ADA COMPLIANT: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

IC RATING: To Be Advised

#### LAMP

LIGHT SOURCE: LED Strip
WATTAGE: 7.4W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (lm): 216
COLOUR TEMP (K): 3000
CRI (Ra): 80

MACADAM ELLIPSE: 2900-3000K

TILT ADJUSTABLE ANGLE (°): 90

ROTATION ADJUSTABLE ANGLE (°): 180

LIFETIME (hrs): 53000

BEAM ANGLE (°): -

#### **ELECTRICAL**

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD: 
SUPPLY FREQUENCY (Hz): 47/63

DRIVER/BALLAST VOLTAGE (V): 90-264

DRIVER LIFETIME (hrs): 20000

EFFICACY (Im/W): 17

### ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: Glass
SHADE/DIFFUSER FINISH Mirror Finish

F MARK: Suitable for mounting

on flammable materials



CODE: 1137004

FINISH: POLISHED CHROME

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





