Digit Led

astro

General

Location: Interior

Class: cULus (Class I)

Location Rating: Dry

Driver Required: Mains 120V

Installation Orientation:Wall Mount - HorizontalFitting Method:Included Junction Box

Main Material: Metal - Zinc

 Dimensions (mm):
 H: 80 W: 190 D: 68

 Dimensions (inch):
 H: 3.15 W: 7.48 D: 2.68

Cut Out Hole (mm/inch): H: 70 W: 175 / H: 2.76 W: 6.89

Recess Depth (mm/inch): 70/2.76

Fire Rating: Cable Length (mm/inch): Gross Weight (lb): 3.34

Ada Compliant: Yes - if installed in compliance with

ADA §307.2, 308, 309.3, 309.

Ic Rating: IC Rated



Light Source: High Powered LED

Wattage: 3.1W

Lamp Included: Yes (Integral)

Maximum Lamp Length (mm/inch):

Luminous Flux (lm):

Colour Temp (K):

Cri (Ra):

Macadam Ellipse:

Tilt Adjustable Angle (°):

Rotation Adjustable Angle (°):

139

2700

2700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

3700

370

Average Lifetime (hrs): To Be Advised

Beam Angle (°): 27

Electrical

Switched: Yes
Dimmable: No
Dimming Method: Supply Frequency (Hz): 50-60
Driver/Ballast Voltage (V): 100-277
Driver Average Lifetime (hrs): 100000
Efficacy (Im/W): 68

Additional Information:

Shade Included: Shade/Diffuser Material: Shade/Diffuser Finish: F Mark: -



CODE: 1323005 FINISH: MATT NICKEL



CODE: 1323009 FINISH: MATT GOLD



CODE: 1323016 FINISH: BRONZE



CODE: 1323029 FINISH: MATT BLACK

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under u.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







