ENNA FLOOR I FD

GENERAL

LOCATION: Interior CLASS: cULus (Class 1)

Dry LOCATION RATING: DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: FITTING METHOD:

MAIN MATERIAL: Metal - Mild Steel DIMENSIONS (mm): H:1190 W:200 D:241 DIMENSIONS (inch): H: 46.85 W: 7.87 D: 9.49

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING:

CABLE LENGTH (mm/inch): 3000/118.11 GROSS WEIGHT (Ib): 15.18

ADA COMPLIANT: Yes - if installed in compliance with ADA 308, 309.3, 309.4

IC RATING:

LAMP

LIGHT SOURCE: High Powered LED

WATTAGE: 4.5W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 124 COLOUR TEMP (K): 2700 90 CRI (Ra): MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°): 330 LIFETIME (hrs): 60000 BEAM ANGLE (°): To Be Advised

ELECTRICAL

SWITCHED: Yes DIMMABLE: DIMMING METHOD: SUPPLY FREQUENCY (Hz): 50/60 DRIVER/BALLAST VOLTAGE (V): 100-120 DRIVER LIFETIME (hrs): EFFICACY (Im/W): 27

ADDITIONAL INFORMATION

SHADE INCLUDED: SHADE MATERIAL: F MARK:







CODE: 1058091 FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, and all rights to such designs and imagery are expressly RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





