GINESTRA 400

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (mm): CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (lb): ADA COMPLIANT:

cULus (Class 1) Dry Mains 120V Ceiling Mount 4" Octagon Box Metal - Mild Steel H: 2041 Ø: 400 H: 80.35 Ø: 15.75 --1800 / 70.87 7.41 Yes - if installed in compliance with ADA 307.4

Interior

IC RATING:

LAMP

| LIGHT SOURCE: | E |
|--------------------------------|----|
| WATTAGE: | 4 |
| RECOMMENDED LAMP: | 1 |
| LAMP INCLUDED: | Ν |
| MAXIMUM LAMP LENGTH (mm/inch): | 1. |
| LUMINOUS FLUX (Im): | L |
| COLOUR TEMP (K): | L |
| CRI (Ra): | L |
| MACADAM ELLIPSE: | L |
| TILT ADJUSTABLE ANGLE (°): | - |
| ROTATION ADJUSTABLE ANGLE (°): | - |
| LIFETIME (hrs): | L |
| BEAM ANGLE (°): | L |

ELECTRICAL

| SWITCHED: | No |
|-----------------------------|----------------|
| DIMMABLE: | Yes |
| DIMMING METHOD: | Lamp Dependent |
| SUPPLY FREQUENCY (Hz): | - |
| DRIVER/BALLAST VOLTAGE (V): | - |
| DRIVER LIFETIME (hrs): | - |
| EFFICACY (Im/W): | Lamp Dependent |

ADDITIONAL INFORMATION:

| SHADE INCLUDED: | - |
|--------------------------|---|
| SHADE/DIFFUSER MATERIAL: | - |
| SHADE/DIFFUSER FINISH | - |
| F MARK: | - |

| E26/Medium |
|------------------------|
| 43W |
| 12W Max LED E26/Medium |
| No |
| 130 |
| Lamp Dependent |
| Lamp Dependent |
| Lamp Dependent |
| Lamp Dependent |
| - |
| |

Lamp Dependent Lamp Dependent



CODE: 1361006 FINISH: MATT BLACK



CODE: 1361009 FINISH: LIGHT GREY



CODE: 1361010 FINISH: MATT WHITE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

