KETA USB (CORD SET)

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (inch): CUT OUT HOLE:

RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): ADA COMPLIANT:

IC RATING:

LAMP

LIGHT SOURCE:	High F
WATTAGE:	3.3W
LAMP INCLUDED:	Yes (Ir
MAXIMUM LAMP LENGTH (mm/inch):	-
LUMINOUS FLUX (Im):	153
COLOUR TEMP (K):	2700
CRI (Ra):	90
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE (°):	84
ROTATION ADJUSTABLE ANGLE (°):	170
LIFETIME (hrs):	60000
BEAM ANGLE (°):	30

ELECTRICAL

SWITCHED:	Yes
DIMMABLE:	No
DIMMING METHOD:	-
SUPPLY FREQUENCY (Hz):	50-60
DRIVER/BALLAST VOLTAGE (V):	100-277
DRIVER LIFETIME (hrs):	30000
EFFICACY (Im/W):	46

ADDITIONAL INFORMATION:

SHADE INCLUDED:	-
SHADE/DIFFUSER MATERIAL:	Plastic
SHADE/DIFFUSER FINISH	Matt Black
F MARK:	Suitable for mounting on flammable materials

Interior cULus (Class 1) Dry Mains 120V Wall Mount - Horizontal & Vertical Direct to Headboard Metal - Zinc H: 256 W: 63 D: 67 H: 10.08 W: 2.48 D: 2.64 Ø: 52mm/2-1/16″/ L: 8.94″ W: 2.05″

63/2.48

3050/120.08 2.44 Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4 Non IC Rated

High Powered LED
3.3W
Yes (Integral)
-
153
2700
90
3-Step
84
170
60000
70



CODE: 1437003 FINISH: MATT NICKEL

CODE: 1437014 FINISH: MATT BLACK



CODE: 1437015 FINISH: MATT WHITE



CODE: 1437016 FINISH: POLISHED CHROME



CODE: 1437017 FINISH: MATT GOLD



CODE: 1437018 FINISH: BRONZE


TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.



256mm/10.08"

