MITSU FLOOR

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (mm): CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): ADA COMPLIANT:

IC RATING:

LAMP

LIGHT SOURCE:	LED E26/Medium
WATTAGE:	12W MAX
RECOMMENDED LAMP:	12W MAX LED E26/MEDIUM
LAMP INCLUDED:	No
MAXIMUM LAMP LENGTH (mm/inch):	126
LUMINOUS FLUX (Im):	Lamp Dependent
COLOUR TEMP (K):	Lamp Dependent
CRI (Ra):	Lamp Dependent
MACADAM ELLIPSE:	Lamp Dependent
TILT ADJUSTABLE ANGLE (°):	90
ROTATION ADJUSTABLE ANGLE (°):	330
LIFETIME (hrs):	Lamp Dependent
BEAM ANGLE (°):	Lamp Dependent

ELECTRICAL

SWITCHED:	Yes
DIMMABLE:	-
DIMMING METHOD:	Lamp Dependent
SUPPLY FREQUENCY (Hz):	-
DRIVER/BALLAST VOLTAGE (V):	-
DRIVER LIFETIME (hrs):	-
EFFICACY (Im/W):	Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED:	Shade Sold Separately	TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.
SHADE/DIFFUSER MATERIAL:	-	ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED.
SHADE/DIFFUSER FINISH	-	ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED
F MARK:	-	UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Interior cULus (Class 1) Dry Mains 120V Ground/Floor

_

Metal - Mild Steel H: 1376 W: 412.5 D: 260 Ø: 130 H: 54.17 W: 16.24 D: 10.24 Ø: 5.12

17.6 Yes - if installed in compliance with ADA 308, 309.3, 309.4

Lamp Dependent Lamp Dependent Yes - Lamp Dependent -	
Yes -	Lamp Dependent
-	Lamp Dependent
-	
-	
-	
- Lamp Dependent -	Yes
Lamp Dependent -	-
-	Lamp Dependent
	-



CODE: 1394033 FINISH: MATT NICKEL CODE: 1394037 FINISH: BRONZE


PAGE. 01/02 ISSUE 1 / 03.09.2020

PRODUCT ELEVATIONS


astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.


Without Shade














With Shade

Ø260mm/10..24"











PAGE. 02/02 ISSUE 1 / 03.09.2020

(4)