MIURA DESK USB

astro

GENERAL

LOCATION:
CLASS:
LOCATION RATING:
DRIVER REQUIRED:
INSTALLATION ORIENTATION:
FITTING METHOD:
MAIN MATERIAL:
DIMENSIONS (mm):
DIMENSIONS (inch):
CUT OUT HOLE (mm/inch):
RECESS DEPTH (mm/inch):
FIRE RATING:
CABLE LENGTH (mm/inch):
GROSS WEIGHT (Ib):
ADA COMPLIANT:

Interior cULus (Class 1) Dry Mains 120V

Metal - Zinc H: 453 W: 150 D: 305 H: 17.83 W: 5.91 D: 12.01

-2250/88.58 7.63 Yes - if installed in compliance with ADA 308, 309.3, 309.4 Non IC Rated

IC RATING:

LAMP

LIGHT SOURCE:	COB LED
WATTAGE:	7.7W
LAMP INCLUDED:	Yes
MAXIMUM LAMP LENGTH (mm/inch):	-
LUMINOUS FLUX (Im):	306
COLOUR TEMP (K):	2700
CRI (Ra):	80
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE (°):	90
ROTATION ADJUSTABLE ANGLE (°):	330
LIFETIME (hrs):	42300
BEAM ANGLE (°):	-

ELECTRICAL

SWITCHED:	Yes
DIMMABLE:	No
DIMMING METHOD:	-
SUPPLY FREQUENCY (Hz):	50/60
DRIVER/BALLAST VOLTAGE (V):	100-127, 100-240
DRIVER LIFETIME (hrs):	100000
EFFICACY (Im/W):	40

ADDITIONAL INFORMATION:

SHADE INCLUDED:	Shade Sold Separately
SHADE/DIFFUSER MATERIAL:	-
SHADE/DIFFUSER FINISH	-
F MARK:	Suitable for mounting on flammable materials



CODE: 1444015 FINISH: MATT NICKEL



CODE: 1444016 FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

Without Shade





With Shade

