

# VETRO TWIN 5748

SKU 1254015

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Matt White	<b>GROSS WEIGHT:</b>	1.50 (lbs)
<b>MAIN MATERIAL:</b>	Metal - Aluminium	<b>CLASS:</b>	cETLus (Class 2)
<b>DIMENSIONS:</b>	H: 175mm W: 90mm D: 80mm H: 6.89" W: 3.54" D: 3.15"	<b>LISTING LOCATION:</b>	Damp
<b>INSTALLATION ORIENTATION:</b>	Ceiling Mount	<b>FITTING METHOD:</b>	Recessed in Drywall Ceiling
<b>CUT OUT HOLE:</b>	L: 6.30" W: 3.15"	<b>ADA COMPLIANT:</b>	Yes
<b>RECESS DEPTH:</b>	150mm/5.91"	<b>IC RATING:</b>	Non IC Rated
<b>FIRE RATING:</b>	Not Applicable	<b>VOLTAGE:</b>	Constant Current 350 (mA)
<b>CABLE LENGTH:</b>	450mm/17.72"		


### LAMP

<b>LIGHT SOURCE:</b>	COB LED	<b>MACADAM ELIPSE:</b>	3-Step
<b>MAXIMUM WATTAGE:</b>	2 x 6W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	20.2 (Degrees)
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>DELIVERED LUMENS:</b>	1231.6 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOR TEMP:</b>	3000 (K)	<b>AVERAGE LIFESPAN:</b>	36,300 (Hrs)
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	15.0		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependant	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	100.95 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	Not Applicable

## ADDITIONAL INFORMATION



BOX QUANTITY x 50

# PRODUCT ELEVATIONS

---

