

FLOS

FU186044 Anodized Champagne

Coordinates Suspension 1

Designed by Michael Anastassiades, 2020



37W - 1920lm - 2700K - CRI > 95

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607034293
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	37
System flux (lm)	1920

Physical

Color	Anodized Champagne
Length (in)	30.79
Cord length (in)	94
Net weight (lb)	4.63
Package volume (in)	1365.1
IP internal	20



Download


[Mounting instructions](#) PDF

Photometric Files

[ULD](#) ZIP

Technical Drawings

[3D](#) ZIP



Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



- | | | |
|-----|--|-----------|
| 01. | Power supply kit for
Arrangements small &
Noctambule | RF0410500 |
| 02. | Led dimmer kit | RF0410300 |



RF0410500

Power supply kit for
Arrangements small &
Noctambule



RF0410300

Led dimmer kit