

FLOS

FU185444 Anodized Champagne

Coordinates Suspension 4

Designed by Michael Anastassiades, 2020



161W - 8830lm - 2700K - CRI> 95

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications


| | |
|-------------------|---------------------|
| EAN | 8059607034354 |
| Mounting | Suspension |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | LED Module |
| Power (W) | 161 |
| System flux (lm) | 8830 |


Physical

| | |
|---------------------|--------------------|
| Color | Anodized Champagne |
| Length (in) | 69.37 |
| Cord length (in) | 94 |
| Net weight (lb) | 17.42 |
| Package volume (in) | 3827.41 |
| IP internal | 20 |



Download

[Mounting instructions](#)  PDF


[Compatible dimmers](#)  PDF

Photometric Files

[ULD](#)  ZIP

Technical Drawings

[3D](#)  ZIP



Photometric

| | |
|--------------------|------------|
| Lighting type | Total |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 95 |

Electrical

| | |
|--------------------|---|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 100-240 |
| Driver | Integrated |
| Dimmable | Yes |
| Dimming type | Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional