
Access

LED panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
2003	3"	6 W	400 lm	80	3000 K	120 V
2004	4"	9 W	600 lm			
2006	6"	11 W	800 lm			

Specifications

Every fixture includes a junction box with an integrated driver
 Over 35,000 hours of service life
 Can be daisy chained
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Frosted lens
 Edge lit technology
 Aluminum construction
 Very low profile
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 Suitable for damp locations
 Refer to website for dimmer compatibility
 5-year warranty

Finish

○ **WH** White

Accessories

REC-TRIM4-BK (2004)
 4" recessed panel trim in black
REC-TRIM4-GD (2004)
 4" recessed panel trim in gold
REC-TRIM4-SN (2004)
 4" recessed panel trim in satin nickel
REC-TRIM6-BK (2006)
 6" recessed panel trim in black
REC-TRIM6-GD (2006)
 6" recessed panel trim in gold
REC-TRIM6-SN (2006)
 6" recessed panel trim in satin nickel
2000-EXT8FT
 8-foot extension cable
2000-EXT20FT
 20-foot extension cable
RFP-23 (2003)
 Rough-in plate
RFP-46 (2004, 2006)
 Rough-in plate
RFP-UNI (2004, 2006)
 Universal rough-in plate

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALs representative for more information.

