


Round flush mount

Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. With 4 sizes to choose from, every application is covered.



WET



COLOR TEMPERATURE



ETL
Intertek



ENERGY STAR

JA8
CERTIFIED*



*Models CFLEDR06, CFLEDR10, and CFLEDR14 only

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
CFLEDR06-CC	6"	11 W	700 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
CFLEDR10-CC	10"	17 W	1000 lm	1200 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
CFLEDR14-CC	14"	26 W	1600 lm	2100 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
CFLEDR18-CC	18"	30 W	2100 lm	2500 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V

Specifications

Integrated dimmable driver
 Over 50,000 hours of service life
 Switch-selectable CCT: 2700 K/
 3000 K/3500 K/4000 K/5000 K in canopy
 Smooth 360° wide spread
 Minimal heat emission
 Frosted lens
 Edge-lit technology
 Cast aluminum construction
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Order example


CFLEDR06-CC-SN
 CFLEDR06-CC 6" round ceiling flush mount
 in a satin nickel finish

Note


Other Color °T and Finishes available, but
 may require MOQ's and longer lead times.
 Please contact your DALs representative
 for more information.




CFLEDR06-CC



CFLEDR10-CC



CFLEDR14-CC



CFLEDR18-CC

