

# LED gimbal

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>LEDDOWNG3</b>	3"	8 W	600 lm	635 lm	90	3000 K	120 V
<b>LEDDOWNG4</b>	4"	8 W	600 lm	635 lm	90	3000 K	120 V
<b>GMB4-3K</b>	4"	11 W	810 lm	1000 lm	90	3000 K	120 V

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Can be daisy chained  
 Superior LED performance and lifespan  
 30° tilting, 360° rotation  
 Minimal heat emission  
 Aluminum construction  
 Low profile  
 40° beam spread  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature:  
 -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Accessories

- RFP-UNI**  
Universal rough-in plate
- RFP-23**  
Rough-in plate for 2" and 3" models
- RFP-46**  
Rough-in plate for 4" and 6" models

### Order example

**LEDDOWNG3-BK**  
 3" gimbal recessed downlight with 600 Lumens at 3000 K in a black finish

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

