


120 V Powerled linear

Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
6009CC	9"	3 W	250 lm	300 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6012CC	12"	4 W	330 lm	400 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6024CC	24"	8 W	675 lm	800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6036CC	36"	12 W	1080 lm	1200 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6048CC	48"	16 W	1300 lm	1800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V

Specifications

Switch-selectable CCT
 Over 50,000 hours of service life
 Dimmable with regular low-voltage electronic dimmers
 Smooth linear wide spread
 Minimal heat emission
 Robust construction
 Multiple fixtures can be linked together (up to 200W)
 Refer to website for dimmer compatibility
 5-year warranty

Note

Junction box model 6000-JB or power cord model 6000-ACPC are required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

Accessories

6000-ACCE06
6" extension cord
6000-ACCE24
24" extension cord
6000-ACCE60
60" extension cord
6000-ACCLR
Kit of left and right L connectors
6000-ACPC
6' power cord
6000-JB
Junction box


Finish

● **SBA** Sandblasted aluminum


Order example

6012CC-SBA
12" LED cove strip with a 4W LED array with 330 lumens at 3000K in a sandblasted aluminum finish

6009CC




6012CC



6024CC



6036CC



6048CC

