



Design By

Naoto Fukasawa

Collection =

Design







Colors & Finishes =



Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Wall support in painted aluminum

Specifications = **Delivered lumens** 392lm Light output ratio 43.56lm/W

Power consumption 9W Led type 8.5W Array*

CCT (Correlated Color Temperature) 2700K

CRI (Color Rendering Index) >90

Life expectancy 50000Hrs


Control type DIMMABLE (On Head) / No Motion Sensor Input Voltage 120-240V

Driver Plug-In

Features & Accessories =


- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions =



Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 7-15/16" x 7-15/16" x 6-3/8" / .77 lbs - 20 cm x 20 cm x 16 cm / .35 kg

Warranty =

1.87 lbs / .85 kg

5 year limited warranty

Luminaire weight =