WAC LIGHTING

Whirl

Mini Light 4CCT

Fixture Type.	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-19408 8"	2700K 3000K 3500K 4000K	BK Black	21 W 21 W 21 W 21 W	1103 1103 1103 1103	1027 1027 1027 1027

Example: **PD-19408-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Like a tornado whirling in space, multiple curves of illumination are backed by a black frame and suspended from a cloud-like canopy. Integrated LEDs provide crisp, clean light tomodern spaces.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- · May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 4000K,3000K,2700K,3500K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum body with silicon diffuser




FINISHES:



Black

LINE DRAWING:



PD-19406