
Effetto round wall 1 narrow beam 3000K white T42121NW08

SPECIFICATIONS

	Design By	Specifications	
	Ernesto Gismondi	Delivered lumens	23lm
		Light output ratio	5lm/W
6	Collection	Power consumption	4.6W
	Outdoor	Led type	4W Array*
		CCT (Correlated Color Temperature)	3000К
		CRI (Color Rendering Index)	>80
		Life expectancy	50000Hrs
		Control type	On/Off
& Finishes		Input Voltage	120V
te RAL9002		Driver	TCI - 1 x DC-12W-700MA-BMU
		BUG Rating	B0-U0-G0
y in aluminum		Features & Accessories • Electronic driver integrated • Standard non dimmable • For dimming options, please consult w	/ith your Artemide Sales Representativ
dy in aluminum		 Electronic driver integrated Standard non dimmable 	vith your Artemide Sales Representativ
		 Electronic driver integrated Standard non dimmable 	rith your Artemide Sales Representativ
		 Electronic driver integrated Standard non dimmable For dimming options, please consult w Packaging 1 Box	
		 Electronic driver integrated Standard non dimmable For dimming options, please consult w Packaging	
ensions		 Electronic driver integrated Standard non dimmable For dimming options, please consult w Packaging 1 Box	
ensions	Luminaire weight 5.6 lbs / 2.54 kg	 Electronic driver integrated Standard non dimmable For dimming options, please consult w Packaging 1 Box 1 x 8-3/8" x 8-3/8" x 8-3/4" / 6.33 lbs - 21 	



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Warranty 5 year limited warranty

