




PRODUCT DESCRIPTION

Reeded glass tubes are paired with ribbed aluminum LED housings in a Gold finish. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications.



*max overall height

MEASUREMENTS

- DIMENSION : 2.25" L x 2.25" W x 17" H
- MAX OAH : 140" OAH
- CANOPY : 4.75" W x 1.5" H x 4.75" L
- HANGING WEIGHT : 2 lb

LAMPING

- INPUT VOLTAGE : 120-277V
- LUMENS : 500 Rated (400 Del.)
- BULB : 1 x 5W LED PCB Integrated , 5W Total
- BULB INCLUDED : (Integrated)
- DIMMABLE : Only at 120V
- CRI : 90 CRI
- COLOR_TEMP : 3000K

FINISHES OPTION



GLASS

Clear Ribbed 144

MATERIAL

Aluminum

RATINGS

cETLus
Dry Location



ADDITIONAL

SLOPE: 30
RATED LIFE 25000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336
P. 626.956.4200 | F. 626.956.4225 | et2online.com