

FLOS

F018E31KU33 Anthracite

In Vitro Unplugged NEW

Designed by Philippe Starck



Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Table
Environments	Outdoor wet location
Light Source Type	LED
LED type	Edge Lighting
Lamp category	LED
Number of heads	1
Power (W)	2.5W
System power (W)	2.5
System flux (lm)	124

Physical

Color	Anthracite
Orientation	Fixed
Net weight (lb)	2.2
IP internal	65




Download

[Family spec sheet](#) ZIP

[Mounting instructions](#) ZIP


Photometric Files

[LDT / IES](#) ZIP




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	106
Beam angle C90-270 (°)	106

Electrical

Insulation class	III
Frequency (Hz)	50-60
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmer on board
Dimming range (%)	1-100
Dimming interface	Dimmer Integrated
Emergency type	No

Notes

When setting up and maintaining the device, be particularly careful not to damage the powder coating.

Damage combined with water may lead to corrosion.

Chemical products may damage the corrosion protection.