

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Frame

Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Title 24	Finish
PD-29828 28"	3000K 90	55W	6334	5131	Yes	AL Brushed Aluminum BK Black

Example: **PD-29828-AL**

DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

FEATURES


- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS


Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%, 0-10V: 100-3%
Rated Life:	50000 Hours
Standards:	ETL, cETL, Title 24: 2019 Damp Location Listed
Construction:	Aluminum body with extruded acrylic diffuser



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Frame

Pendant 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Title 24	Finish
PD-29858 58"	3000K 90	58W	7160	5800	Yes	AL Brushed Aluminum BK Black

Example: **PD-29858-AL**

DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

FEATURES

- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%, 0-10V: 100-3%
Rated Life:	50000 Hours
Standards:	ETL, cETL, Title 24: 2019 Damp Location Listed
Construction:	Aluminum body with extruded acrylic diffuser



FINISHES



LINE DRAWING

