

INSTALLATION INSTRUCTION

Class 2 Power Supply

EN-2460D-C-P

WAC LIGHTING

Responsible Lighting®

CAUTION – TO REDUCE RISK OF FIRE AND ELECTRICAL SHOCK

- Always turn off power at main switch prior to installation.
- Intended for installation by a qualified electrician.
- System is intended for installation in accordance with National Electric Code, and local regulations. Consult with local inspector to assure compliance.

Max Load	60W
Input Voltage	120-240V 60Hz
Input Current	1.2A
Output Current	2.5A
Output Voltage	24V DC
Case Temp	40°C to 55°C
Ambient Temp	-4° to 122°F (-10°C to 70°C)
Minimum Load	1.5W

FEATURES:

- Power Supply short circuit protection with auto-reset.
- Overload protection with auto-reset.
- Automatic thermal regulation.
- Soft start delay to preserve bulb life, for use with controller

INSTALLATION

- DC power supply must be installed away from heat sources and accessible for service
- DC power supply is UL listed. Plug into the building line voltage and connect the other side with down stream electrical product.



EN-2460D-C-P

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Ave • Ontario, CA 91761
Phone (800) 526.2588 • Fax (800) 526.2585